



115° C RISE

480 DELTA PRIMARY VOLTS — 208Y/120 SECONDARY VOLTS — MAY BE USED ON A 4 WIRE 480Y/277 VOLTS SUPPLY— 3Ø, 60 Hz
DOE/NRCAN 2019 Compliant

kVA	Catalog Number	Height (Inches)(Cm.)	Width (Inches)(Cm.)	Depth (Inches)(Cm.)	Weight (Lbs.)(Kg.)	Mounting Type (Wall)(Floor)	Knockouts (Inches)(Cm.)	Optional Electrostatic Shield	Wiring Diagrams	Design Figures
15.0	T3015K0013BSF	25.50 (64.8)	24.39 (61.9)	19.37 (49.2)	300 (136.0)	F ①	NA	STD.	22	E
30.0	T3030K0013BSF	25.50 (64.8)	24.39 (61.9)	19.37 (49.2)	360 (163.3)	F ①	NA	STD.	22	E
45.0	T3045K0013BSF	25.50 (64.8)	24.39 (61.9)	19.37 (49.2)	500 (226.8)	F ①	NA	STD.	22	E
75.0	T3075K0013BSF	29.41 (74.7)	28.15 (71.5)	22.37 (56.8)	600 (272.2)	F ①	NA	STD.	22	E
112.5	T3112K0013BSF	35.47 (90.1)	31.90 (81.0)	26.88 (68.2)	938 (425.5)	F	NA	STD.	22	E
150.0	T3150K0013BSF	41.52 (105.4)	32.90 (83.5)	29.87 (75.9)	1213 (550.2)	F	NA	STD.	22	E
225.0	T3225K0013BSF	45.60 (115.8)	39.50 (100.3)	35.50 (90.1)	2298 (1042.3)	F	NA	STD.	22	E
300.0	T3300K0013BSF	45.60 (115.8)	39.50 (100.3)	35.50 (90.1)	2319 (1051.9)	F	NA	STD.	22	E
500.0	T3500K0013BSF	57.80 (147.0)	45.60 (115.8)	41.50 (105.4)	4156 (1885.1)	F	NA	STD.	22	G

① Wall mounting brackets are available for these sizes, refer to page 41.

80° C RISE

480 DELTA PRIMARY VOLTS — 208Y/120 SECONDARY VOLTS — MAY BE USED ON A 4 WIRE 480Y/277 VOLTS SUPPLY— 3Ø, 60 Hz
DOE/NRCAN 2019 Compliant

kVA	Catalog Number	Height (Inches)(Cm.)	Width (Inches)(Cm.)	Depth (Inches)(Cm.)	Weight (Lbs.)(Kg.)	Mounting Type (Wall)(Floor)	Knockouts (Inches)(Cm.)	Optional Electrostatic Shield	Wiring Diagrams	Design Figures
15.0	T3015K0013BSB	25.50 (64.8)	24.39 (61.9)	19.37 (49.2)	378 (171.5)	F ①	NA	STD.	22	E
30.0	T3030K0013BSB	25.50 (64.8)	24.39 (61.9)	19.37 (49.2)	550 (249.5)	F ①	NA	STD.	22	E
45.0	T3045K0013BSB	29.41 (74.7)	28.15 (71.5)	22.37 (56.8)	755 (342.5)	F	NA	STD.	22	E
75.0	T3075K0013BSB	35.47 (90.1)	31.90 (81.0)	26.88 (68.2)	1054 (478.1)	F	NA	STD.	22	E
112.5	T3112K0013BSB	41.52 (105.4)	32.90 (83.5)	29.87 (75.9)	1454 (659.5)	F	NA	STD.	22	E
150.0	T3150K0013BSB	41.52 (105.4)	32.90 (83.5)	29.87 (75.9)	1729 (784.3)	F	NA	STD.	22	E

For Copper wound transformers consult factory.

① Wall mounting brackets are available for these sizes, refer to page 41.

All Wiring Diagrams begin on page 35.

