



#19500 AME PREMIUM HYDRAULIC OIL, 1 GALLON



- Recommended for use with all AME hydraulic tools
- Operating temperature rating to -40 degrees Fahrenheit/Celsius
- Anti-wear, anti-sludge, anti-rust, anti-foam additives
- Meets FMC Hi-Performance, Hydraulic Oil, Grade 32 requirements
- Can be shipped via UPS

#19510 AME PREMIUM HYDRAULIC OIL, 55 GALLON



- Recommended for use with all AME hydraulic tools
- Operating temperature rating to -40 degrees Fahrenheit/Celsius
- Anti-wear, anti-sludge, anti-rust, anti-foam additives
- Meets FMC Hi-Performance, Hydraulic Oil, Grade 32 requirements
- Can be shipped via UPS



#26148 OTR TIRE SEALANT



Because the seating of O-rings is not always consistent, this fibrous liquid product will maintain air pressure in the tire by stopping rim leaks and vent leaks. Faster OTR tire and rim removal, reduced downtime, labor and expenses.

- Seals punctures of up 1/4"
- Lubricates rims and tire for quick and easy removal
- Eliminates rust on rims
- Tires run cooler
- Water based for easy clean-out
- Will not freeze
- Environmentally friendly and safe product, recognized by the United States E.P.A.