




Hammer Unions

4,000 psi cwp – 6,000 psi test

 FIGURE 400 Threaded Ends Black Nut/Red Subs	Size		Item		Unit Weight		A		B		C		TPI	Material	
	NPS	Dn			lbs	kg	in	mm	in	mm	in	mm		Nuts	Subs
  Ideal for manifold and pumping service.	2	50	Union Complete		11.05	5.01	5.225	132.72	3.000	76.20	7.125	180.98	3 STD	SF	SF
			Nut		5.60	2.54									
			Male Sub		2.65	1.20									
			Female Sub		2.80	1.27									
	3	80	Union Complete		20.00	9.07	6.110	155.19	4.250	107.95	8.750	222.25	3 STD	SF	SF
			Nut		8.50	3.85									
			Male Sub		5.50	2.49									
	4	100	Union Complete		29.15	13.22	8.200	208.28	5.275	133.99	9.160	232.66	3 STD	SF	SF
			Nut		10.15	4.60									
			Male Sub		8.85	4.01									
			Female Sub		10.15	4.60									

- Warnings:** 1. Do not make up or break out Unions in pressurized lines.
 2. Always use good safety practices, including use of safety glasses, when making up or breaking out Unions.

TPI = Threads per inch SF = Steel Forging

PROJECT INFORMATION		APPROVAL STAMP	
Project:		<input type="checkbox"/> Approved	
Address:		<input type="checkbox"/> Approved as noted	
Contractor:		<input type="checkbox"/> Not approved	
Engineer:		Remarks:	
Submittal Date:			
Notes 1:			
Notes 2:			



Catawissa™
PERFORMANCE UNDER PRESSURE

HAMMER UNIONS



Catawissa™
PERFORMANCE UNDER PRESSURE



Material

ASTM A29, A105

Full Traceability:

All Catawissa Oilfield Hammer Unions are fully traceable and are available with complete mill certifications upon request.

Interchangeability:

All Catawissa Oilfield Unions are machined to rigid quality standards ensuring that like components of the same size, figure number and pressure rating are fully interchangeable in the field. Catawissa Oilfield Unions are interchangeable with most leading union manufacturers.

Full Range of End Connections:

Catawissa Oilfield Hammer Unions are available in threaded ends, as well as buttweld and non-pressure seal ends. When you choose Catawissa you receive the utmost in quality, the widest selection and unmatched on-time deliveries.



Gatawissa Quick Reference Chart

STANDARD SERVICE												
Fig No.	CWP	TEST	API Color Code		Pipe Size (in.)							
			SUB	NUT	1"	1¼"	1½"	2"	2½"	3"	4"	6"
100	1,000	1,500	Yellow	Black								
200	2,000	3,000	Gray	Blue								
206	2,000	3,000	Gray	Blue								
211	2,000	3,000	Light Blue	Gray								
300	2,000	3,000	Yellow	Gray								
301	3,000	4,500	Green	Black								
400	4,000	6,000	Red	Black								
602	6,000	9,000	Orange	Black								
607	6,000	9,000	Silver	Yellow								
1502	15,000	22,500	Red	Blue								