

AE Series Pin and Sleeve Plugs, Connectors and Receptacles

Weatherproof

600 Vac, 250 Vdc. Pressure Wire Terminals.

NEC:
Rated for Ordinary (Unclassified) Locations

Applications

- Designed to supply power to portable or fixed electrical equipment such as:
 - Welders
 - Generators
 - Compressors
 - Pumps
 - Similar apparatus
- Suitable for use in locations where a weatherproof enclosure is required such as:
 - Shipping docks
 - Ports
 - Ship to shore applications



Features

- Available in 30, 60, and 100 Amp units.
- Contacts exert constant pressure along the entire contact surface, providing electrical continuity. Solid brass contacts with beryllium copper springs.
- Choice of receptacle types: weatherproof spring door or raintight screw cap.
- Plug with clamp ring has neoprene gasket. Ring threads onto screw cap receptacle to provide raintight assembly when properly tightened.
- Cable clamps prevent strain on cables and allow easy cable replacement.
- Mounting box gasket protects receptacle from moisture.
- Insulating blocks provide high degree of dielectric and mechanical strength and lowest moisture absorption, lowest arc tracking.
- Choice of several mounting boxes permits different types of installations.
- Floating-type plug contacts self-align to receptacle contacts.
- Available in two grounding styles: Style 1 (shell only) and Style 2 (shell and extra pole).
- Grounding detent springs in Style 1 and Style 2.
- Grounding strap provided in Style 2 permits extra pole grounding.
- Longer ground contact in Style 2 "makes first and breaks last."

Standard Materials

- Plug, connector, receptacle and mounting box housings: copperfree (4/10 of 1% max.) aluminum
- Insulation blocks: fiber glass reinforced phenolic
- Contacts: brass

Standard Finishes

- Aluminum plug, receptacle, connector, and mounting box housings: epoxy powder coat
- Insulating blocks and contacts: natural finish

Options

- Reverse Service: useful where a "hot" plug feeds a dead receptacle. Reverse service is often used for generator applications where the receptacle houses a dead plug interior. Plug houses an energized receptacle interior, which has recessed male contacts to reduce danger of accidental touching. Suffix **-RS** to receptacle or connector.

NEC Compliances

- UL Standard: UL 1682

AE Series 30 Amp Pin and Sleeve Receptacles Connectors and Plugs

Weatherproof

600 Vac, 250 Vdc. Pressure Wire Terminals. Wire Size Range: #14—#8

NEC:

Rated for Ordinary (Unclassified) Locations



Grounding Style	Wire/Pole	Spring Door Receptacle Only	Screw Cap Receptacle Only	Connector Body Only	Clamping Ring Plug	Plug Cable Dia. (Inches)
Style 1 (Shell Only)	2W, 2P	AE321	AE327	APR3251	AEP3251	.625 to .750
	3W, 3P	AE331	AE337	APR3351	AEP3351	.625 to .750
	4W, 4P	AE341	AE347	APR3451	AEP3451	.625 to .750
Style 2 (Shell and Extra Pole)	2W, 3P	AE332	AE338	APR3361	AEP3361	.625 to .750
	3W, 4P	AE342	AE348	APR3461	AEP3461	.625 to .750

AE Series Mounting Boxes



Hub Size (Inches)	AEE	AERH	AERC	AERA
1/2	AEE13	AERH13	AERC13	AERA13
3/4	AEE23	AERH23	AERC23	AERA23
1	AEE33	AERH33	AERC33	AERA33

30 Amp Interiors ①



Grounding Style	Wire/Pole	Interior Style 1		Interior Style 2	
		Receptacle	Plug	Receptacle	Plug
Style 1 (Shell Only)	2W, 2P	AEI-321	AEPI-321	—	—
	3W, 3P	AEI-331	AEPI-331	—	—
	4W, 4P	AEI-341	AEPI-341	—	—
Style 2 (Shell and Extra Pole)	2W, 3P	—	—	AEI-332	AEPI-332
	3W, 4P	—	—	AEI-342	AEPI-342

① Pins and sleeves are not sold separately. Must purchase as a replacement interior.