

# EFD/EFDB and EDS Series Factory Sealed Control Stations

## Explosionproof, Dust-Ignitionproof

### NEC:

Class I, Division 1 and 2, Groups B\*, C, D

Class II, Division 1 and 2, Groups E, F, G

Class III

NEMA 3, 7CD, 9EFG

### Applications

- Push buttons and selector switches are used in conjunction with contactors or magnetic starters for remote control of motors. They provide circuit control and/or selection.
- Pilot lights provide visual assurance that an electrical function is being performed at a remote or local location.
- EFD/EFDB and EDS factory sealed control stations confine arcing of device within the enclosure, preventing ignition of ignitable atmospheres during control operation of motors and other equipment.
- Used in classified areas where flammable vapors, gases or highly combustible dusts are present.
- For installation in chemical and petrochemical plants, refineries, and other process industries.

### Features

- EFD/EFDB Push Buttons and Selector Switches
  - Eliminate need for adding sealing fittings and compound at each conduit entrance.
  - Heavy-duty push buttons, 10 Amp, 600 Vac rated.
  - Dozens of possible combinations of push buttons, pilot lights and selector switches.
  - Smooth, rounded integral bushing in each EFD/EFDB hub protects conductor insulation.
  - Accurately tapped, tapered hubs for tight, rigid joints and ground continuity.
  - Stainless steel push button shaft operates within stainless steel bushing assuring long, maintenance free operation.
  - Push button and selector switch contacts are silver cadmium oxide which are "sealed" in lower phenolic chamber isolated from corrosive elements. Assures positive contact and long, trouble-free operation.
  - Enclosed stainless steel helper spring prevents accidental operation of push button in severe vibration installations.
  - Push button models also available with dust cap for use in areas where excessive dust, moisture or corrosive conditions are encountered.
  - Corrosion resistant captive stainless steel hex head cap screws hold EFKB covers to body.
  - All EFD/EFDB momentary push buttons are supplied with lockout type guards as standard. Hole in guard will accept locks with up to 1/4" hasp. Permits locking of push button to prevent unauthorized operation.
  - Clearly marked terminals with brass screws assure quick, easy wiring.
- EFD/EFDB Pilot Lights
  - Factory sealed pilot lights supplied with red jewel/guard assembly and 120 Vac/Vdc, 50/60 Hz, 6 Watt, Type 6S6 lamp.
  - Models also available in combination with factory sealed push buttons and selector switches.
- EFD/EFDB Selector Switches
  - Factory sealed selector switches furnished with nylon cam-operated, heavy-duty push buttons for either 2-position or 3-position maintained contact operation.
  - High thermal and arc resistance, high dielectric strength.
- EDS Push Buttons
  - Factory sealed — eliminates need for adding sealing fittings and compound at each conduit entrance.
  - Heavy duty, 10 Amp, 600 Vac.
  - Switch is enclosed in separate sealing chamber.



EFD/EFDB Push Button



EFD/EFDB Photocontrol



EFD Combination Pilot Light and Push Buttons



EDS Rocker Arm Push Button



EFD/EFDB Push Button with Dust Cap



EFD/EFDB Pilot Light



EFD/EFDB Selector Switch



EFD/EFDB Maintained Push Button

- Sealing chamber has smooth, double flanges that mate both to cover and mounting enclosure to provide flame-tight joints.
- Pigtail leads from push buttons are factory sealed in sealing well.
- Stainless steel hex head screws attach sealing chamber to cover and mounting enclosure.
- Side rocker arm push button has lockout holes.
- EFD/EFDB backbox supplied with internal ground screw.

### Standard Materials

- EFD/EFDB control stations: malleable iron body with copperfree (4/10 of 1% max.) aluminum cover
- SPBB push button: copperfree (4/10 of 1% max.) aluminum upper barrel and phenolic lower barrel with nylon plastic button (dust cap models have neoprene buttons)
- SPLN/SPLS pilot light: copperfree (4/10 of 1% max.) aluminum guard and body assembly; steel clamping ring; and tempered glass jewel
- SSBA selector switch: copperfree (4/10 of 1% max.) aluminum operator mechanism, nylon cam, and sealed phenolic contact block
- EDS control stations: malleable iron body and cover; copperfree (4/10 of 1% max.) aluminum sealing chamber; and nylon operating handle

♦ Select items suitable for Class I, Division 1 and 2, Groups B, C and D; Class II, Groups E, F and G and Class III. See product selection pages for suitable items.

# EFD/EFDB and EDS Series Factory Sealed Control Stations

## Explosionproof, Dust-Ignitionproof

### NEC/CEC:

Class I, Division 1 and 2, Groups B\*, C, D

Class II, Division 1 and 2, Groups E, F, G

Class III

NEMA 3, 7CD, 9EFG

### Standard Finishes

- EFD/EFDB control stations: body, triple-coat—(1) zinc electroplate, (2) chromate, and (3) epoxy powder coat
- SPBB push button, SPLN/SPLS pilot light and SSBA selector switch: natural finish
- EDS control stations: body and cover: triple-coat—(1) zinc electroplate, (2) chromate, and (3) epoxy powder coat sealing chamber, natural finish

### Options

- 1- or 2-gang copperfree (4/10 of 1% max.) aluminum bodies and covers available. Add suffix — **A**.
- Three position selector switches with modified operation.
  - Momentary contact right position, spring return to center, maintained contact left position. Add suffix — **SRC**.
  - Momentary contact left position, spring return to center, maintained contact right position. Add suffix — **SLC**.
  - Alternate contacts add suffix — **ALT**.
- EFD/EFDB selector switch lockout locks two or three position handle in any position. Add suffix — **LD**.
- Push button front operated mushroom head (momentary contact): Order by suffixes for desired color as follows:
  - Red — **NMRBRE**
  - Green — **NMRBGR**
  - Black — **NMRBBL**
- EFD/EFDB pilot light jewel/guard assembly. Order by suffixes if color desired is other than red, as follows:
  - Amber — **JGBA**
  - Blue — **JGBB**
  - Clear — **JGBC**
  - Green — **JGBG**;
  - Opal — **JGBO**
- For colored LED jewel/guard assembly, order by suffixes:
  - Red — **LEDR**
  - Green — **LEDG**
  - Amber — **LEDA**
- EFD/EFDB pilot light transformers for single pilot light per gang. Order by suffix:

Primary Voltage	Lamp Voltage	Suffix
220	120	-TR-2
277	120	-TR-3
440	120	-TR-4
550	120	-TR-5

- EFD and EDS units may be supplied with brazed hubs as 3-, 4-, and 5-gang in a variety of hub configurations. See Ordering Information page for how to order these and other "custom" units by adding suffixes to mounting body catalog numbers.
- Securing Rod for EFD/EFDB Push Button Lockout Guard. Add suffix — **SR**.
- NPBRKT** Nameplate Mounting Bracket to make circuit description/identification easy.
  - Pre-drilled holes in bottom of bracket allow direct mounting to control stations with existing cover bolts.
  - Pre-drilled holes in middle of bracket allow mounting of customer's circuit identification nameplate; epoxy glue may also be used for mounting (phenolic nameplate not included).
  - Bracket eliminates costly field installation of drilling and tapping to accommodate circuit identification nameplate.
  - Brackets fit side-by-side on 2-, 3- and 4-gang boxes and 3-devices.

### NEC Certifications and Compliances

- UL Standards: UL 508, UL 698, UL 1203
- cULus Listed: E10449, E81751

### Related Products

- For Hazardous Location Photocontrols, see *Lighting Section*.

### Illustrated Features



EDS factory sealed rocker arm push button control station — shows separate sealing chamber and device construction. Rocker arm has holes for lock.




Securing Rod for EFD/EFDB Push Button Lockout Guard — available as an optional item as catalog number NBL-SR (single guard only) or add Suffix — SR to push button catalog number. Lockout Guard, furnished as standard with the EFD/EFDB push button, may also be padlocked.



SPBB factory sealed push button used in EFD/EFDB Series — standard type and unit with dust cap.

### SPBB Design Features



Appleton

CONTROLS: NEC/CEC EXPLOSIONPROOF CONTROL STATIONS AND SWITCHES

◆ Select items suitable for Class I, Division 1 and 2, Groups B, C and D; Class II, Groups E, F and G and Class III. See product selection pages for suitable items.

# EFD/EFDB and EDS Series Factory Sealed Control Stations

Explosionproof, Dust-Ignitionproof

**NEC/CEC:**


Class I, Division 1 and 2, Groups B\*, C, D

Class II, Division 1 and 2, Groups E, F, G

Class III

NEMA 3, 7CD, 9EFG

**Catalog Numbering Guide**



**Full Catalog # EFDCT10-J1U2-JGBG-SNPTESTQ-U2-SNPTESTQ-SNPRUNQ**

Feed-Thru Tandem Box with 1" Hubs.  
 In Gang #1: 2 Momentary Push Buttons and a Green Pilot Light.  
 In Gang #2: 2 Momentary Push Buttons with One Securing Rod.  
 With Special "Test" and "Run" Push Button Nameplates.

**Options**

Options Description	Suffix
Momentary Push Button Securing Rod	SR
Selector Switch Lockout	LD
Spring Return From Right Selector Switch (3 Positions Only)	SRC
Spring Return From Left Selector Switch (3 Positions Only)	SLC
Alternate Contacts Selector Switch	ALT
Change One Red Lens to Green Lens	JGBG
Change One Red Lens to Opal Lens	JGBO
Change One Red Lens to Amber Lens	JGBA
Change One Red Lens to Blue Lens	JGBB
Change One Red Lens to Clear Lens	JGBC
Add 220/120 Vac Transformer (J1 Device Only)	TR2
Add 277/120 Vac Transformer (J1 Device Only)	TR3
Add 440/120 Vac Transformer (J1 Device Only)	TR4
Add 550/120 Vac Transformer (J1 Device Only)	TR5
Change One Red Pilot to Red LED	LEDR
Change One Red Lens to Green LED	LEDG
Change One Red Lens to Amber LED	LEDA
Add Red Mushroom Head to Momentary Push Button	NMRBRE
Add Black Mushroom Head to Momentary Push Button	NMRBBL
Add Green Mushroom Head to Momentary Push Button	NMRBGR
Locking Guard for Maintained Push Button	SMPBLG

\* Select items suitable for Class I, Division 1 and 2, Groups B, C and D; Class II, Groups E, F and G and Class III. See product selection pages for suitable items.

# EFD/EFDB and EDS Series Factory Sealed Control Stations

EFKB Covers With Pilot Lights and/or Push Buttons. For EFD Bodies

**NEC/CEC:**

Class I, Division 1 and 2, Groups C, D  
 Class II, Division 1 and 2, Groups E, F, G  
 Class III

Description		Nameplate Marking	Catalog Number
<b>Cover complete with Push Button – Factory Sealed – Momentary Contact ①②</b>			
		<i>For use on standard EFD bodies</i>	
	1 Circuit Universal		Start/Stop
	2 Circuit Universal		Start/Stop
<b>EFKB-U1</b>	<b>EFKB-U2</b>		
<b>Cover complete with Red Mushroom Head Push Button – Factory Sealed – Maintained Contact ①②</b>			
		<i>For use on standard EFD bodies – Emergency Stop Nameplate</i>	
	1 Circuit Universal (Red)		Emergency Stop
			<b>EFKB-UM1</b>
<b>Cover complete with Pilot Lights – Factory Sealed – Momentary Contact ①②</b>			
		<i>6 Watt, 120 Vac, Type 6S6 Lamp. For use on standard EFD bodies</i>	
			
	One pilot light (red jewel ③) and two universal push buttons		Start/Stop
<b>J1U2</b>	<b>J1U1</b>		<b>EFKB-J1U2</b>
	One pilot light (red jewel ③) and one universal push button		Start/Stop
	One pilot light (red jewel ③) and one universal push button–dust cap		Start/Stop
<b>J1</b>	<b>J2</b>		<b>EFKB-J1DU1</b>
	One pilot light (red jewel ③)		Start/Stop
	Two pilot lights (red jewels ③)		Start/Stop
<b>J1</b>	<b>J2</b>		<b>EFKB-J1</b>
	Photocontrol relay cover (120 Vac)		<b>EFKB-PC120</b>
		Photocontrol relay cover (208-277 Vac)	<b>EFKB-PC277</b>
<b>PC</b>			

① All covers are copperfree aluminum. Supplied with four captive stainless steel bolts.

② When installed on a single gang box the cover assembly is suitable for use in Group B environments but will not be marked Group B.

③ Colored jewels, pilot lights and LED's listed under accessories and parts