

Mercmaster™ III Low Profile Compact Fluorescent Luminaires

Enclosed and Gasketed. For Hazardous and Wet Locations

Compact Fluorescent listed for simultaneous exposure to combustible dusts and flammable gases or vapors.

NEC/CEC:

Class I, Division 2, Groups A, B, C, D
 Class I, Zone 2, AEx nA nR IIC (Z2)
 Class II, Division 1 and 2, Groups E, F, G
 Class III

NEC/CEC:

Simultaneous Exposure (Class I, Division 2/
 Class II, Division 1)
 Fixtures Outside Type (Salt Water)
 Type 4X
 IP66

CEC:

Class I, Zone 2, Ex nR IIC (Z)

Item	Description	Catalog Number
Replacement Optic Gaskets — Silicone rubber		
	Globe and Polymeric Refractor Gasket	VPGL-GK
	Glass Refractor Gasket	KRF-GK
Replacement Lamp		
	Mercmaster III Low Profile Compact Fluorescent	
	Lamp Type	Lamp Base
	Wattage	Catalog Number
	PL-T	GX24q-3
	PL-T	GX24q-3
	PL-T	GX24q-4
	PL-T	GX24q-5
		26
		32
		42
		57
		PLT26
		PLT32
		PLT42
		PLT57 ③
Replacement Socket		
	For 26 W, 32 W and 42 W PLT Lamps listed above	PLT32RS
	For 57 W PLT Lamp	PLT57RS ③
Three-Way Exit Sign ①		
	Epoxy enameled steel – 152.4 mm (6”) high red lettering	CJEXRN
	Mounts to Globe Ballast Housing in place of guard.	
Single Sided Exit Sign ①		
	Epoxy enameled steel – 152.4 mm (6”) high red lettering	AEXR-15R
	Mounts to Globe Ballast Housing in place of guard	
Retrofit Pendant Mounting Adapter		
	Permits use of Mercmaster III pendant hood with 3/4” hub on existing V-51 mounting hood	LPAD-1
Fuse Kit ②		
	2 Amp time delay fuse	MLF2

① Consult your local sales representative for classified area suitability. Not listed for Zone 2 areas.

② Canadian Electrical Code does NOT allow fusing in hazardous locations.

③ Certified to meet the Canadian Electrical Code (CEC) only.