

360° Swivel Conduit Unions

Explosionproof, Dust-Ignitionproof

UNILETS™ for Use with Threaded Rigid Metal Conduit and IMC.

NEC/CEC:

Class I, Division 1 and 2, Groups C, D
Class I, Zone 1 and 2, Groups IIA, IIB
Class II, Division 1 and 2, Groups E, F, G
Class III

Application

- Allows conduit to be joined at any angle.

Features

- Explosionproof, dust-ignitionproof.
- Smooth, rounded integral bushing in each hub protects conductor insulation.
- Accurately tapped, tapered NPT threads for tight, rigid joints and ground continuity.
- Threaded for rigid conduit or IMC.

Standard Materials

- Gray iron

Standard Finishes

- Zinc electroplate




NEC/CEC Compliances and Certifications

- UL Standard: 886 (500-503 and 505)
- UL Listed: E34997
- CSA Standard: C22.2 No. 30
- CSA Certified: 009795

Size (Inches)	Dimensions in Millimeters (Inches)		Catalog Number
	Overall Length	Maximum Diameter	
Flexible/Swivel Elbows — Full 360°			
1/2	101.6 (4.00)	47.6 (1.88)	UNAF50
3/4	114.3 (4.50)	50.8 (2.00)	UNAF75
1	133.4 (5.25)	63.5 (5.50)	UNAF100



Dimensions in Millimeters (Inches)



Size (Inches)	A	B	C	D	E Throat Ø	F Ø	G NPT	H UN Thread	I
1/2	101.60 (4.00)	76.20 (3.00)	76.20 (3.00)	47.63 (1.88)	15.08 (0.59)	66.68 (2.63)	12.70 — 355.60 (0.50 — 14.00)	50.80 — 6.35 (2.00 — 0.25)	3.97 (0.16)
3/4	114.30 (4.50)	84.37 (3.32)	84.37 (3.32)	52.39 (2.06)	19.84 (0.78)	74.61 (2.94)	19.05 — 355.60 (0.75 — 14.00)	63.5 — 304.80 (2.50 — 12.00)	3.97 (0.16)
1	133.35 (5.25)	8							