

Mercmaster™ III Low Profile Compact Fluorescent Luminaires

Enclosed and Gasketed. For Hazardous and Wet Locations

Compact Fluorescent listed for simultaneous exposure to combustible dusts and flammable gases or vapors.

NEC/CEC:

Class I, Division 2, Groups A, B, C, D
Class I, Zone 2, AEx nA nR IIC (Z)
Class II, Division 1 and 2, Groups E, F, G
Class III

NEC/CEC:

Simultaneous Exposure (Class I, Division 2/
Class II, Division 1)
Fixtures Outside Type (Salt Water)
Type 4X
IP66

CEC:

Class I, Zone 2, Ex nR IIC (Z)

Item	Description	Catalog Number ③
White Polyester Reflectors		
	For Globe Fixtures	
	Standard Dome	KR2-ST
	30° Angle	KR2-AN
Standard Dome		
	For Glass Refractor Fixtures ①	
	Standard Dome	CMR-4ST ②
	30° Angle	CMR-4AN ②
30° Angle Dome		
Prismatic Glass Globes — Heat-Resistant ③		
	Clear	VPGL-2HR
	Amber ④	VPGL-2AM
	Blue ④	VPGL-2BL
	Green ④	VPGL-2GR
	Red ④	VPGL-2RE
	Clear — 57/114 Watt ⑤	VPGL-4HR
Closed Prismatic Glass Refractors — All Heat-Resistant ③		
	NEMA Type I	LPG-R1
	NEMA Type III	LPG-R3
	NEMA Type V	LPG-R5
Closed Prismatic Polymeric Refractors — Not Listed for Class I, Zone 2 Areas		
	NEMA Type II	LPRF-2CP
	NEMA Type III	LPRF-3CP
	NEMA Type IV	LPRF-4CP
	NEMA Type V	LPRF-5CP
Guards		
	Globe Guard	KGU2
	Glass Refractor Guard	KRG2
	Globe Guard — 57/114 W ⑤	KPGU400
Globe Guard for 57 W Only		

① Fixtures with refractors are not UL Listed when used with reflectors.

② Standard dome reflectors may interfere with bottom conduit entry if used with KPST and KPWB mounting hoods.

③ Silicone or Teflon coated globes are available. Contact your local sales representative.

④ Non hazardous rated globes for special applications.

⑤ Certified to meet the Canadian Electrical Code (CEC) only.