

Impenetrable Purge Barrier

- Excellent Barrier for Retaining Noble Gas (Argon or Argon/Helium Mix)

Flexible & Robust

- For Use on Stainless, Duplex and Chromium Steels & Titanium Alloys
- Can Be Punctured for Gas Inlets and Outlets with Little Risk of Tearing
- High Resistance to Pressure, Allowing for Greater Positive Pressure to be Maintained in Weld Area

Impenetrable Purge Barrier

- For Ease of Viewing During Welding Process

Ease of Removal

- Rapidly Dissolves in Hot or Cold Water
- Leaves No Residue In The Pipeline

Safe

- Suitable for Nuclear, Aerospace, and Other Applications

SPECIFICATIONS FOR LIQUIFILM® WATER SOLUBLE PURGE FILM AND ADHESIVE

LiquiFilm® Types and Sizes

PRODUCT	ITEM NO.	DESCRIPTION	DIMENSIONS		CASE PACK
			ENGLISH	METRIC	
	ASWF-1/20RG	Liquifilm® Water Soluble Film Kit	39" x 65'	1 m x 20 m	12
	ASWF-1/20B	Liquifilm® Water Soluble Film Brick Format	39" x 65'	1 m x 20 m	12
	AWSG-500	Liquifilm® Water Soluble Adhesive	16 fl oz	500 ml/bottle	24
	AWSG-250	Liquifilm® Water Soluble Adhesive	8 fl oz	250 ml/bottle	48

For additional product information, quotations and ordering, please contact:


Distributed By:

Aquasol Corporation

80 Thompson Street
N. Tonawanda, NY 14120 USA

Toll Free: 1.800.564.WELD (9353)
Phone: 716.564.8888
Fax: 716.564.8889

Email: info@aquasolcorporation.com
aquasolwelding.com



American Welding Society
Sustaining Company Member



MADE IN THE USA