

XEX severe duty, three phase, totally enclosed, 230/460 volts, 460 and 575 volts, C-Face

1 thru 200 Hp

IP55



Features:

- Robust cast iron construction
- Regreasable bearings all frames
- 304 stainless steel nameplates
- Inverter Duty nameplate
- Division 2, Class I, Groups A, B, C, D markings on nameplate
- Locked bearing to allow mounting in any configuration

Applications:

- Chemical, oil & gas
- Pulp & paper, forest products
- Metals & foundries
- Cement, aggregate & above ground mining
- Food processing
- Power generation
- Water & wastewater treatment

Hp	RPM	NEMA Frame	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
C-Face, Foot Mounted											
1	1800	143TC	CECP3581T	1,727	SDM	13.38	67	87.5	230/460	1.5	1
		143TC	CECP3581T-5	1,727	SDM	13.38	60	85.5	575	1.2	1
1 1/2	1200	145TC	CECP3582T	1,903	SDM	13.38	75	82.5	230/460	1.7	1
		145TC	CECP3584T	1,762	SDM	13.38	72	88.5	230/460	2.1	1
1 1/2	1800	145TC	CECP3584T-5	1,762	SDM	13.38	72	88.5	575	1.7	1
		1200	CECP3667T	2,212	SDM	16.68	99	87.5	230/460	2.5	1
2	1800	145TC	CECP3587T	1,833	SDM	13.38	76	88.5	230/460	2.8	1
		145TC	CECP3587T-5	1,833	SDM	13.38	76	88.5	575	2.3	1
2	1200	184TC	CECP3664T	2,235	SDM	16.68	113	88.5	230/460	3.2	1
		3600	CECP3660T	2,257	SDM	16.68	112	88.5	230/460	3.4	1, 30
3	1800	182TC	CECP3661T	2,366	SDM	16.68	114	89.5	230/460	4.1	1
		182TC	CECP3661T-5	2,366	SDM	16.68	114	89.5	575	3.2	1
3	1200	213TC	CECP3764T	3,257	SDM	20.24	187	90.2	230/460	4.5	1, 30
		3600	CECP3663T	2,741	SDM	16.68	121	90.2	230/460	5.7	1, 30
5	1800	184TC	CECP3665T	2,403	SDM	16.68	130	89.5	230/460	6.5	1
		184TC	CECP3665T-5	2,403	SDM	16.68	130	90.2	575	5.2	1
5	1200	215TC	CECP3768T	3,298	SDM	20.24	226	90.2	230/460	7.3	1, 30
		3600	CECP3769T	3,686	SDM	20.24	173	89.5	230/460	8.6	1
7 1/2	1800	213TC	CECP3770T	3,144	SDM	20.24	170	91.7	230/460	9.5	1
		213TC	CECP3770T-5	3,144	SDM	20.24	170	91.7	575	7.5	1
7 1/2	1200	254TC	CECP2276T	4,808	SDM	25.28	305	91	230/460	10.7	1, 30
		3600	CECP3771T	3,901	SDM	20.24	203	92.4	230/460	11	1, 30
10	1800	215TC	CECP3774T	3,700	SDM	20.24	231	92.4	230/460	12.5	1
		215TC	CECP3774T-5	3,700	SDM	20.24	231	91.7	575	9.8	1
10	1200	256TC	CECP2332T	6,151	SDM	25.28	323	91	230/460	14.2	1, 30
		3600	CECP2294T	5,509	SDM	25.28	307	91.7	230/460	17.2	1, 30
15	1800	254TC	CECP2333T	5,256	SDM	25.28	297	92.4	230/460	18.1	1, 30
		254TC	CECP2333T-4	5,256	SDM	25.28	296	92.4	460	18.1	1
15	1200	254TC	CECP2333T-5	5,256	SDM	25.28	296	92.4	575	14.6	1
		284TC	CECP4100T	7,633	SDM	27.93	435	91.7	230/460	21	1, 30
20	3600	256TC	CECP4106T	6,273	SDM	25.28	333	91	230/460	22	1, 30
		256TC	CECP2334T	5,571	SDM	25.28	339	93	230/460	24	1, 30
20	1800	256TC	CECP2334T-4	5,571	SDM	25.28	336	93	460	24	1
		256TC	CECP2334T-5	5,571	SDM	25.28	336	93	575	19.2	1
25	1200	286TC	CECP4102T	10,034	SDM	27.93	460	91.7	230/460	26	1
		3600	CECP4107T	7,652	SDM	26.56	396	91.7	230/460	28	1, 30
25	1800	284TC	CECP4103T-4	7,362	SDM	27.93	440	93.6	460	30	1
		286TC	CECP4103T	7,362	SDM	27.93	449	93.6	230/460	30	1, 30
25	1200	286TC	CECP4103T-5	7,362	SDM	27.93	449	93.6	575	24	1
		324TC	CECP4111T	10,808	SDM	30.28	626	93	230/460	32	1, 30
30	3600	286TSC	CECP4108T	9,063	SDM	26.56	454	91.7	230/460	34	1
		286TC	CECP4104T	8,497	SDM	27.93	478	93.6	230/460	36	1, 30
30	1800	286TC	CECP4104T-4	8,497	SDM	27.93	475	93.6	460	36	1
		286TC	CECP4104T-5	8,497	SDM	27.93	475	93.6	575	28	1
30	1200	326TC	CECP4117T	13,554	SDM	30.28	640	93	230/460	39	1, 30

(a) See notes on inside back flap. Cast iron frame

Information
General purpose Single phase
General purpose Three phase
Severe duty
Large Motors and Generators
Washdown duty
Explosion proof
Pump
HVAC
Farm duty