



Customer information packet

CNEDM3546T

1HP, 1770RPM, 3PH, 60HZ, 143TC, 3522M, TENV, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	TENV
Frame	143TC
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	1.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ 230.0 V @ 60 HZ
Agency Approvals	CCSA US CSA EEV NEMA PREMIUM NEMA_PREMIUM UR
Ambient Temperature	40 °C
Auxillary Box	No Auxillary Box
Auxillary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Constant Torque Speed Range	6
Current @ Voltage	3.340 A @ 230.0 V 3.300 A @ 208.0 V 1.670 A @ 460.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	85.5 %
Electrically Isolated Bearing	Not Electrically Isolated

Part detail

Revision	B
Type	AC
Mech. spec.	35E4320
Base	
Status	PRD/A
Elec. spec.	35WGZ818
Layout	35LYE4320
Eff. date	07-14-2022
CD Diagram	CD0005
Poles	04
Leads	9#18
Proprietary	False
Created date	01-10-2022

Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	1.7 a
Insulation Class	F
Inverter Code	Inverter Ready
KVA Code	M
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	2700 rpm
Motor Lead Quantity/Wire Size	9 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3522M
Mounting Arrangement	F1
Number of Poles	4
Overall Length	13.23 IN
Power Factor	66
Product Family	Dirty Duty Plus
Pulley End Bearing Type	Sealed Bearing
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	0.875 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1770 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor

Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP3504

CAT NO	CNEDM3546T									
SPEC.	35E4320Z818G1					ENCL	TENV			
FRAME	143TC	HP	1							
VOLTS	230/460									
FLA	3.34/1.67				I.P.	56				
RPM	1770	RPM MAX				2700				
HZ	60	PH	3	CLASS			F			
SER.F.	1.15	DES	B	CC		010A				
NEMA-NOM-EFF	85.5									
RATING	40C AMB-CONT									
DE BRG	6205	ODE BRG				6203				
GREASE	POLYREX EM									
C HP FR	60	C HP TO			90					
CT HZ FROM	6	CT HZ TO			60	VT HZ FROM	6	VT HZ TO	60	
SER.NO										
	SFA 3.5/1.75									

AC Induction Motor Performance Data

Record # 89784

Typical performance - not guaranteed values

Winding: 35WGZ818-R002			Type: 3522M		Enclosure: TENV			
Nameplate Data			460 V, 60 Hz: High Voltage Connection					
Rated Output (HP)		1	Full Load Torque		2.99 LB-FT			
Volts		230/460	Start Configuration		direct on line			
Full Load Amps		3.34/1.67	Breakdown Torque		16.6 LB-FT			
R.P.M.		1770	Pull-up Torque		7.42 LB-FT			
Hz	60	Phase	3	Locked-rotor Torque		10.32 LB-FT		
NEMA Design Code		B	KVA Code	M	Starting Current		16.1 A	
Service Factor (S.F.)		1.15	No-load Current		1.23 A			
NEMA Nom. Eff.		85.5	Power Factor		66	Line-line Res. @ 25°C		14.4 Ω
Rating - Duty		40C	AMB-CONT		Temp. Rise @ Rated Load		63°C	
S.F. Amps		3.5/1.75	Temp. Rise @ S.F. Load		71°C			
			Locked-rotor Power Factor		60.4724			
			Rotor inertia		0.159 lb-ft²			

Load Characteristics 460 V, 60 Hz, 1 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	27	43	56	66	73	78	72
Efficiency	70.8	81.2	84.5	85.9	85.8	85.2	85.5
Speed	1793	1786	1781	1773	1766	1758	1768
Line amperes	1.25	1.34	1.49	1.67	1.87	2.12	1.75

ABB Motors and Mechanical Inc.

WINDING # 35WGZ818

Typical performance - not guaranteed values.

1 HP 3 PH 60 HZ 1770 RPM 460 V 3522M

TORQUES (LB-FT): PO=16.6 PU=7.42 LR=10.32 LRA=16.1





