

XEX severe duty, three phase, totally enclosed, 230/460 volts, 460 and 575 volts, foot mounted

Hp	RPM	NEMA Frame	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)	
230/460 volts & 460 volts (continued)												
100	3600	405TS	ECP4402T	23,038	SDM	35.04	1283	94.1	230/460	110	1	
		405TS	ECP4402T-4	23,038	SDM	35.04	1272	94.1	460	110	1	
	1800	405T	ECP4400T-4	22,695	SDM	38.20	1296	95.4	460	112	1	
		405T	ECP4400TR-4	23,818	SDM	38.20	1326	95.4	460	112	1, 5	
		405TS	ECP4400TS-4	22,695	SDM	35.04	1304	95.4	460	112	1	
		444T	ECP4409T-4	29,726	SDM	44.75	1871	95	460	119	1	
	1200	444T	ECP4409TR-4	31,656	SDM	44.75	1871	95	460	119	1, 5	
		445T	ECP4420T-4	44,236	SDM	44.75	1905	93.6	460	125	1	
	125	3600	444TS	ECP4412T	27,071	SDM	41.08	1957	95	230/460	138	1
			444TS	ECP4412T-4	27,071	SDM	41.08	1901	95	460	137	1
1800		444T	ECP4410T-4	26,831	SDM	44.75	1950	95.4	460	144	1	
		444T	ECP4410TR-4	28,761	SDM	44.75	1950	95.4	460	144	1, 5	
1200		445T	ECP4411T-4	33,582	SDM	44.75	2146	95	460	146	1	
		445T	ECP4411TR-4	35,512	SDM	44.75	2146	95	460	146	1, 5	
900		447T	ECP4421T-4	48,448	SDM	48.24	2330	95	460	149	1	
		447T	ECP4413T-4	31,737	SDM	40.83	2017	95	460	164	1	
150		3600	445TS	ECP4406T-4	31,432	SDM	44.75	2190	95.8	460	169	1
			445T	ECP4406TR-4	33,362	SDM	44.75	2190	95.8	460	169	1, 5
	1800	445T	ECP44156T-4	37,862	SDM	48.24	2546	95.8	460	170	1	
		447T	ECP44156TR-4	39,791	SDM	48.24	2585	95.8	460	170	1, 5	
	900	449T	ECP4422T-4	55,666	SDM	53.24	3051	95	460	188	1	
		447TS	ECP4416T-4	37,579	SDM	44.48	2436	96.2	460	213	1	
	200	3600	447T	ECP4407T-4	37,812	SDM	48.24	2545	96.2	460	222	1
			447T	ECP4407TR-4	39,739	SDM	48.24	2621	96.2	460	222	1, 5
		1800	447TS	ECP4407TS-4	37,812	SDM	44.48	2573	96.2	460	222	1
			449T	ECP44206T-4	49,596	SDM	53.24	3104	95.8	460	225	1
1200		449T	ECP44206TR-4	51,523	SDM	53.24	3091	95.8	460	225	1, 5	
		449T	ECP4423T-4	70,655	SDM	53.24	3179	95	460	248	1	
250		3600	449TS	ECP44252T-4	57,466	SDM	49.48	2633	95.8	460	269	1
			449T	ECP4408T-4	47,983	SDM	53.24	2981	96.2	460	276	1
		1800	449T	ECP4408TR-4	49,910	SDM	53.24	2995	96.2	460	276	1, 5
			449T	ECP44256T-4	69,188	SDM	53.24	3090	96.2	460	283	1
	1200	449T	ECP44256TR-4	71,115	SDM	53.24	3093	95.8	460	287	1, 5	
		5008L	ECP502506-PP	52,434	ISD	60.17	3682	95.8	460	296		
	300	900	L449T	ECP49258T-4	85,552	SDM	60.13	3430	95	460	288	1, 99
			449TS	ECP44302T-4	83,987	SDM	49.48	2789	96.2	460	318	1
		3600	5008S	ECP503002-PP	51,123	ISD	60.17	3791	95.8	460	327	
			449T	ECP44304T-4	66,134	SDM	53.24	3061	96.2	460	334	1
1800		449T	ECP44304TR-4	68,063	SDM	53.24	3048	96.2	460	334	1, 5	
		5008S	ECP503004-PP	48,412	ISD	60.17	3902	96.2	460	330		
350		1200	L449T	ECP49306T-4	100,809	SDM	60.13	3125	95.8	460	340	1, 99
			5010L	ECP503006-PP	61,525	ISD	67.05	4277	95.8	460	356	
		900	L449T	ECP49308T-4	91,261	SDM	60.13	4089	95	460	378	14, 99
			5010L	ECP503008-PP	72,641	ISD	67.05	4564	95	460	369	
	3600	449TS	ECP44352T-4	87,854	SDM	49.48	2965	95.8	460	370	1	
		5008S	ECP503502-PP	56,605	ISD	60.17	4012	95.8	460	380		
	400	1800	L449T	ECP49354T-4	102,998	SDM	60.21	3543	96.2	460	384	1, 99
			5008L	ECP503504-PP	53,604	ISD	60.17	3902	96.2	460	397	
		1200	5010L	ECP503506-PP	66,656	ISD	67.05	4607	95.8	460	416	
			900	5012L	ECP503508-PP	80,076	ISD	74.00	5291	95.0	460	437
3600		L449TS	ECP44402T-4	117,940	SDM	56.72	3700	96.2	460	420	1	
		5010S	ECP504002-PP	62,199	ISD	67.05	4431	95.8	460	439		
450		1800	L449T	ECP49404T-4	106,057	SDM	60.34	3682	96.2	460	435	1, 99
			5008L	ECP504004-PP	58,901	ISD	60.17	4299	96.2	460	462	
		1200	5012L	ECP504006-PP	73,399	ISD	74.00	5005	95.8	460	476	
			900	5012L	ECP504008-PP	85,950	ISD	74.00	5667	95	460	480
	1800	L449T	ECP49454T-4	109,031	SDM	60.34	3720	96.2	460	460	1, 99	
		5010L	ECP504504-PP	65,068	ISD	67.05	4564	96.2	460	511		
	500	1200	5012L	ECP504506-PP	77,821	ISD	74.00	5445	95.8	460	534	
			900	5012L	ECP504508-PP	89,115	ISD	74.00	5886	95	460	560
		3600	5010S	ECP505002-PP	75,156	ISD	67.05	4431	95.8	460	542	
			1800	5010L	ECP505004-PP	72,615	ISD	67.05	4564	96.2	460	561
1200		5012L	ECP505006-PP	80,796	ISD	74.00	5754	95.8	460	606		
		900	5012L	ECP505008-PP	94,612	ISD	74.00	5886	95	460	610	

(a) See notes on inside back flap. Cast iron frame

Information

General purpose Single phase

General purpose Three phase

Severe duty

Large Motors and Generators

Washdown duty

Explosion proof

Pump

HVAC

Farm duty