

Paint free, three phase, totally enclosed, C-Face

1/2 thru 10 Hp

IP55



Features:

- Sealed ball bearings
- Neoprene gaskets
- Rotating non-contact labyrinth seal
- 300 series stainless steel motor frame, base, shaft and hardware
- No exterior paint
- 3 year warranty

Applications:

- Food processing
- Packaging
- Outdoor applications

Hp	RPM	NEMA Frame	Enclosure	Catalog Number	List Price	Disc. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
Foot mounted												
1/2	3600	56C	TENV	CSWDM3537	1,204	WDP	11.06	29	70	208-230/460	0.9	2, 30
	1800	56C	TENV	CSWDM3538	1,177	WDP	11.06	27	80	230/460	0.8	1, 12, 30
	1200	56C	TENV	CSWDM3539	1,647	WDP	12.06	38	78.5	208-230/460	1	1, 12, 30
3/4	3600	56C	TENV	CSWDM3541	1,263	WDP	11.06	36	80	208-230/460	1.1	1, 12, 30
	1800	56C	TENV	CSWDM3542	1,359	WDP	11.06	30	78.5	230/460	1.4	1, 12, 30
	1200	56C	TENV	CSWDM3543	1,988	WDP	12.94	47	81.5	208-230/460	1.4	30
1	1800	56C	TENV	CESWDM3546	1,894	WDP	12.06	40	85.5	230/460	1.5	1, 30
		143TC	TENV	CESWDM3546T	1,853	WDP	12.12	39	87.5	230/460	1.5	1, 30
1 1/2	1800	56C	TENV	CESWDM3554	1,933	WDP	12.94	50	86.5	230/460	2.1	30
		145TC	TENV	CESWDM3554T	1,984	WDP	13.00	50	86.5	230/460	2.1	30
2	3600	145TC	TEFC	CESWDM3555T	2,350	WDP	14.16	52	86.5	208-230/460	2.5	1, 30
		56C	TEFC	CESWDM3558	2,287	WDP	13.24	45	86.5	230/460	2.9	1, 30
3	1800	145TC	TEFC	CESWDM3558T	2,435	WDP	15.54	56	88.5	230/460	2.8	1, 30
		3600	145TC	TEFC	CESWDM3559T	2,892	WDP	15.54	62	86.5	208-230/460	3.7
5	1800	182TC	TEFC	CESWDM3611T	2,979	WDP	16.56	79	89.5	230/460	4	1, 30
		3600	184TC	TEFC	CESWDM3613T	3,667	WDP	18.06	88	90.2	230/460	5.7
7 1/2	1800	184TC	TEFC	CESWDM3615T	3,466	WDP	18.06	92	89.5	230/460	6.7	1, 30
		3600	213TC	TEFC	CESWDM3709T	4,629	WDP	18.68	134	91	230/460	8.3
10	1800	213TC	TEFC	CESWDM3710T	4,265	WDP	19.81	135	91.7	230/460	9.5	1
		3600	215TC	TEFC	CESWDM3711T	5,131	WDP	19.81	154	91.7	230/460	10.6
10	1800	215TC	TEFC	CESWDM3714T	4,853	WDP	21.31	165	91.7	230/460	12	1
		Footless										
1/2	1800	56C	TENV	VSWDM3538	1,164	WDP	11.06	28	80	230/460	0.8	1, 12, 30
3/4	1800	56C	TENV	VSWDM3542	1,347	WDP	11.06	31	78.5	230/460	1.4	1, 12, 30
		56C	TENV	VESWDM3546	1,803	WDP	12.06	39	85.5	230/460	1.5	1, 30
1	1800	143TC	TENV	VESWDM3546T	1,810	WDP	12.12	43	87.5	230/460	1.5	1, 30
		56C	TENV	VESWDM3554	1,963	WDP	12.95	47	86.5	230/460	2.1	30
1 1/2	1800	145TC	TENV	VESWDM3554T	1,963	WDP	13.00	49	86.5	230/460	2.1	30
		2	1800	145TC	TEFC	VESWDM3558T	2,241	WDP	15.56	55	88.5	230/460

(a) See notes on inside back flap.

Information

General purpose Single phase

General purpose Three phase

Severe duty

Large Motors and Generators

Washdown duty

Explosion proof

Pump

HVAC

Farm duty