

102012C, Copper Shear Bolt Stirrup Connector

By Burndy
Catalog # 102012C



CPI Copper Stirrup Connectors are designed for connecting to copper conductors. Stirrups are intended to protect the main line conductor from damage and arcing as hot line clamps are connected and disconnected. During installation, when proper spring tension and torque is achieved, the shear head bolt will break off giving the install a positive indication of a corrected completed connection.

Features

- Easy to remove and re-use without damaging the conductor
- Heavy duty tin plated bail has a large loop to allow for multiple connection positions while also eliminating galvanic reaction
- Easy to install with standard socket or impact wrench, requires no special tools
- Easily adaptable to standard hot stick tools
- Remains permanently locked through fault current or power surges
- Excellent option for emergency restoration

General

Catalog Number	102012C
Type	Stirrups

UPC	621945675339
-----	--------------

Dimensions

Dimension - Bail Size	1/0
-----------------------	-----

Conductor Related

Conductor Range	Main Conductor: #6 Sol-#4 Str Cu, 1/0 Bail
-----------------	---

Product Assets

[Catalogs - BURNDY Master Catalog - Section J - OH Distribution / Transmission](#)
[Installation Manuals - Hot-Stick Stirrup Installation Instructions](#)
[Specifications - 102012C](#)