



FD678D16TOQ, Substation - Copper Stud Connector

By Burndy
Catalog # [FD678D16TOQ](#)

Copper Stud Connectors



Features

- High copper alloy stud connector allows bolting cable and tubing terminals to equipment studs
- Hex head captured bolts provide one-wrench installation
- One pad contact surface is on centerline of stud, pad is finished on both sides, all pads are 4-hole NEMA drilling

Application

Substation

Specifications

Certification - ETL	No
Certification - UL Recognized	No
Standards - RoHS Compliance	EX
Status	
Certification - cULus	No
UL Listed	No
Certification - CSA Approved	No

Conductor

Conductor - Connection Combination	Stud to Pad
------------------------------------	-------------

Configuration

Connector Type	Stud Connector
----------------	----------------

Dimensions

Dimension - Height mm	0 mm
-----------------------	------

General

Plated	N
Material - Hardware	DURIUM™ Silicon Bronze
UPC	781810480915
Type	Studs
Material	Copper Alloy
Plating Type	Unplated
UPC 12 Digit	781810480915
UPC 14 Digit GTIN	00781810480915

Logistics

Minimum Pack Quantity	1
Pallet Quantity	1
Carton Quantity	1

Product Assets

[Catalog \[English\]](#)