



FD702D16T0, Substation - Copper Stud Connector

By Burndy
Catalog # [FD702D16T0](#)

Copper Stud Connectors

Features

- For use on stud to pads
- Allows for bolting cable and tubing terminals to equipment studs
- Hex captured bolts provide one-wrench installation

Application

Substation

Specifications

Standards - RoHS Compliance EX
Status

Conductor

Conductor - Connection Stud to Pad
Combination

Configuration

Physical Attribute - Pad In-line
Orientation
Physical Attribute - Pad 4x4 - 4 holes
Configuration
Physical Attribute - Number of 4
Holes
Connector Type Stud Connector

Dimensions

Dimension - Pin Diameter inch 3.000 in
Dimension - Pin Diameter 3 in
fraction

Dimension - Pad Width inch 4.00 in
Dimension - Height mm 0 mm
Dimension - Bolt Size fraction 5/8
Dimension - B Length fraction 2-7/8 in
Dimension - F Width Center to 1.75 in
Center inch
Dimension - L Length Overall 210 mm
mm
Dimension - B Length inch 2.88 in
Dimension - D inch 4.00 in
Dimension - Thread Size 5/8 in
Dimension - Length Overall 8.26 in
inch

General

Plated N
Material - Hardware DURIUM™ Silicon Bronze
UPC 781810453889
Type Studs
Material Copper Alloy
Plating Type Unplated
UPC 12 Digit 781810453889
UPC 14 Digit GTIN 00781810453889

Logistics

Minimum Pack Quantity 1
Pallet Quantity 1
Carton Quantity 1

Product Assets

[Catalog \[English\]](#)