



FD705D16, Substation - Copper Stud Connector

By Burndy
Catalog # [FD705D16](#)

Cast Cu Alloy Substation Stud Connector, Bolted, Stud to Pad, 3-1/4" -12 Stud, 230 kV, Silicon Bronze H/W, 3000 Amp



Features

- For use on stud to pads
- Allows for bolting cable and tubing terminals to equipment studs
- Hex captured bolts provide one-wrench installation

Application

Substation

Specifications

Certification - ETL	No
Certification - UL Recognized	No
Standards - RoHS Compliance	EX
Status	
Certification - cULus	No
UL Listed	No
Certification - CSA Approved	No

Conductor

Conductor - Connection Combination	Stud to Pad
------------------------------------	-------------

Configuration

Connector Type	Stud Connector
----------------	----------------

Dimensions

Dimension - Pin Diameter inch	3.250 in
Dimension - Pin Diameter fraction	3-1/4 in
Dimension - Height mm	0 mm

General

Plated	N
Material - Hardware	DURIUM™ Silicon Bronze
UPC	781810003374
Type	Studs
Material	Copper Alloy
Plating Type	Unplated
UPC 12 Digit	781810003374
UPC 14 Digit GTIN	00781810003374

Logistics

Minimum Pack Quantity	1
Pallet Quantity	1
Carton Quantity	1

Product Assets

[Catalog \[English\]](#)