



FD70F16CG1, Substation - Copper Stud Connector

By Burndy
Catalog # [FD70F16CG1](#)

Copper Stud Connectors



Features

- For use on stud to pads
- Allows for bolting cable and tubing terminals to equipment studs
- Hex captured bolts provide one-wrench installation

Application

Substation

Specifications

Standards - RoHS Compliance	UI
Status	
Certification - CSA Approved	No

Conductor

Conductor - Connection Combination	Stud to Pad
------------------------------------	-------------

Configuration

Physical Attribute - Pad Orientation	In-line
Physical Attribute - Pad Configuration	6x4 - 6 holes
Physical Attribute - Number of Holes	6

Connector Type	Stud Connector
----------------	----------------

Dimensions

Dimension - Pin Diameter inch	3.000 in
Dimension - Pin Diameter fraction	3 in
Dimension - Pad Width inch	6.00 in
Dimension - Height mm	0 mm
Dimension - D inch	4.00 in
Dimension - Threads per inch	12

General

Plated	N
Material - Hardware	DURIUM™ Silicon Bronze
UPC	621945253254
Type	Studs
Material	Copper Alloy
Plating Type	Unplated
UPC 12 Digit	621945253254
UPC 14 Digit GTIN	00621945253254

Logistics

Minimum Pack Quantity	1
-----------------------	---

Product Assets

[Catalog \[English\]](#)