



FD73F16, Substation - Copper Stud Connector

By Burndy
Catalog # [FD73F16](#)

Copper Stud Connectors



Features

- For use on stud to pads
- Allows for bolting cable and tubing terminals to equipment studs
- Hex captured bolts provide one-wrench installation

Application

Substation

Specifications

Standards - RoHS Compliance UI
Status

Conductor

Conductor - Connection Stud to Pad
Combination

Configuration

Physical Attribute - Pad In-line
Orientation
Physical Attribute - Pad 6x4 - 6 holes
Configuration
Physical Attribute - Number of 6
Holes
Connector Type Stud Connector

Dimensions

Dimension - Pin Diameter inch	4.500 in
Dimension - Pin Diameter fraction	4-1/2 in
Dimension - Pad Width inch	6.00 in
Dimension - Height mm	0 mm
Dimension - Bolt Size fraction	5/8
Dimension - B Length fraction	3 in
Dimension - B Length inch	3.00 in
Dimension - D inch	4.00 in
Dimension - Thread Size	5/8-12
Dimension - Threads per inch	12

General

Plated	N
Material - Hardware	DURIUM™ Silicon Bronze
UPC	781810444610
Type	Studs
Material	Copper Alloy
Plating Type	Unplated
UPC 12 Digit	781810444610
UPC 14 Digit GTIN	00781810444610

Logistics

Minimum Pack Quantity	1
-----------------------	---

Product Assets

[Catalog \[English\]](#)