



K22A36U2, AL Universal Terminal, 4-Conductor, 2-Hole

By Burndy
Catalog # [K22A36U2](#)

4 Conductor, #2-600 kcmil Class B&C, #2-500 kcmil Class G,H,I,K, DLO, 2-Hole, 3/8" holes, 1.38" Spacing, tin plated

Features

- Dual rated panelboard lugs
- Constructed from high strength, extruded aluminum alloy
- Electro tin-plated to provide low contact resistance

Application

For Aluminum and Copper Conductors

Specifications

Buy American Compliant	No
Buy America(n) Qualified	BABA Compliant (All status valid till December 2026)
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance	EX
Status	
Certification - UL Listed Direct Burial	No
UL Listed	Yes
Certification - CSA Approved	Yes

Conductor

Conductor - AL Str Size	• 2 AWG • 1 AWG • 1/0 AWG • 2/0 AWG • 3/0 AWG • 4/0 AWG • 250 kcmil • 266 kcmil • 300 kcmil • 336 kcmil • 350 kcmil • 397 kcmil • 400 kcmil • 450 kcmil • 477 kcmil • 500 kcmil • 550 kcmil • 556 kcmil • 600 kcmil
Conductor - AL Str Size Range	2 Str. - 600 Kcmil
Conductor - Copper Str Size	• 2 AWG • 1 AWG • 1/0



- 2/0 AWG
- 3/0 AWG
- 4/0 AWG
- 250 kcmil
- 300 kcmil
- 350 kcmil
- 400 kcmil
- 450 kcmil
- 500 kcmil
- 550 kcmil
- 600 kcmil

Number Of Conductors	4
Conductor Type	• AL C Str-Size • CU C Str-Size
Conductor - Copper Str Size Range	2 Str. - 600 Kcmil

Configuration

Physical Attribute - Number of Screws	4
Physical Attribute - Number of Holes	2
Connector Type	Stacked

Dimensions

Dimension - Pad Width inch	2.49 in
Package Height	0.000 in
Dimension - Height mm	77 mm
Dimension - Height inch	3.03 in
Dimension - Height fraction	3 in
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in
Dimension - L Length Overall mm	125 mm
Dimension - Hole Size mm	10 mm
Dimension - Hole Size inch	0.41 in
Dimension - Stud Size inch	3/8 in
Dimension - Bolt Hole Size inch	0.38 in
Dimension - Bolt Size fraction	3/8
Dimension - Width mm	64 mm
Dimension - Width inch	2.49 in
Dimension - D inch	2.31 in
Dimension - N inch	0.38 in
Dimension - Length Overall inch	4.91 in

Force Related

Installation Torque Recommended in-lb	375 LBS/in	UPC 12 Digit UPC 14 Digit GTIN	781810370346 00781810370346
General		Logistics	
Product Family	MECHANICAL	Minimum Pack Quantity	1
Material - Hardware	Aluminum	Pallet Quantity	576
Physical Attribute - Screw Type	Allen	Carton Quantity	18
Plated	Yes	Operational	
Sub Brand	UNIVERSAL TERM	Temperature Rating	194
Product Type	Terminal	Product Assets	
UPC	781810370346	Catalog [English]	
Type	Bolted Lugs & Terminals		
Material	Aluminum		
Plating Type	Tin		

