




K2A31U, AL Universal Terminal, 2-Conductor, 1-Hole

By Burndy
Catalog # [K2A31U](#)



2 Conductor, #6 AWG-350 kcmil Class B&C, #6 AWG-300 kcmil Class G,H,I,K, DLO, 1-Hole, 1/2" Stud, Tin Plated, Dual Rated

Features

- Dual rated panelboard lugs
- Constructed from high strength, extruded aluminum alloy
- Electro tin-plated to provide low contact resistance

Application

For Aluminum And Copper Conductors

Specifications

EU RoHS Indicator	No
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	NC
Certification - UL Listed Direct Burial	No
UL Listed	Yes
Certification - CSA Approved	Yes

Conductor

Conductor - AL Str Size	• 6 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG • 1/0 AWG • 2/0 AWG • 3/0 AWG • 4/0 AWG • 250 kcmil • 266 kcmil • 300 kcmil • 336 kcmil • 350 kcmil
Conductor - AL Str Size Range	6 Str.- 350 Kcmil
Conductor - Copper Str Size	• 6 AWG • 5 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG • 1/0 • 2/0 AWG • 3/0 AWG

Conductor Size	• 4/0 AWG • 250 kcmil • 300 kcmil • 350 kcmil
Number Of Conductors	6 AWG-350 KCMIL
Conductor Type	2
Conductor - Copper Str Size Range	• AL C Str-Size • CU C Str-Size 6 Str.- 350 Kcmil

Configuration

Physical Attribute - Number of Holes	1
Connector Type	Parallel Set-Screw

Dimensions

Dimension - Pad Width inch	1.94 in
Package Height	2.250 in
Dimension - Height mm	32 mm
Dimension - Height inch	1.26 in
Dimension - Height fraction	1.25 in
Package Weight	1.690 lb.
Package Length	8.100 in
Package Width	3.450 in
Dimension - L Length Overall mm	73 mm
Dimension - Width fraction	1-47/50 in
Dimension - Hole Size mm	14 mm
Dimension - Hole Size inch	0.56 in
Dimension - Screw Size inch	3/8
Dimension - Stud Size inch	1/2 in
Dimension - Bolt Hole Size inch	0.50 in
Dimension - Bolt Size fraction	1/2
Dimension - Width mm	49 mm
Dimension - Width inch	1.94 in
Dimension - D inch	1.69 in
Dimension - N inch	0.88 in
Dimension - Length Overall inch	2.88 in

Force Related

Installation Torque Recommended in-lb	275 LBS/in
---------------------------------------	------------

General

Material - Hardware	Aluminum
Physical Attribute - Screw Type	Slot
Plated	N
Sub Brand	UNIVERSAL TERM
UPC	781810600153
Type	Bolted Lugs & Terminals
Material	Aluminum
Plating Type	Tin plated
UPC 12 Digit	781810600153
Hardware Type	3/8 UNC Slotted Set Screw
UPC 14 Digit GTIN	00781810600153

Logistics

Pallet Quantity	3264
Carton Quantity	102

Operational

Temperature Rating	194
--------------------	-----

Product Assets

[Catalog \[English\]](#)



A Hubbell brand