



K2A44U, AL Universal Terminal, 2-Conductor, 1-Hole

By Burndy
Catalog # [K2A44U](#)

2-Conductor, 500-1000 kcmil Class B&C, 500-750 kcmil Class G,H,I,K,
DLO, 1-Hole, 5/8" Stud, Dual Rated, Tin Plated

Features


- Dual rated panelboard lugs
- Constructed from high strength, extruded aluminum alloy
- Electro tin-plated to provide low contact resistance

Specifications

Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance	NC
Status	
Certification - UL Listed Direct Burial	No
UL Listed	Yes
Certification - CSA Approved	Yes

Conductor

Conductor - AL Str Size	• 500 kcmil • 550 kcmil • 556 kcmil • 600 kcmil • 636 kcmil • 650 kcmil • 700 kcmil • 715 kcmil • 750 kcmil • 795 kcmil • 800 kcmil • 874 kcmil • 900 kcmil • 954 kcmil • 1000 kcmil
Conductor - AL Str Size Range	500 -1000 Kcmil
Conductor - Copper Str Size	• 500 kcmil • 550 kcmil • 600 kcmil • 700 kcmil • 750 kcmil • 800 kcmil • 850 kcmil • 900 kcmil • 1000 kcmil
Conductor Size	500-1000 KCMIL



Number Of Conductors	2
Conductor Type	• AL C Str-Size • CU C Str-Size
Conductor - Copper Str Size Range	500 -1000 Kcmil

Configuration

Physical Attribute - Number of Holes	1
Connector Type	Parallel Set-Screw

Dimensions

Dimension - Pad Width inch	3.52 in
Package Height	2.250 in
Dimension - Height mm	49.5 mm
Dimension - Height inch	1.95 in
Dimension - Height fraction	2 in
Package Weight	3.480 lb.
Package Length	10.000 in
Package Width	5.600 in
Dimension - L Length Overall mm	89 mm
Dimension - Width fraction	3-13/25 in
Dimension - Hole Size mm	17 mm
Dimension - Hole Size inch	0.66 in
Dimension - Screw Size inch	3/8
Dimension - Stud Size inch	5/8 in
Dimension - Bolt Hole Size inch	0.63 in
Dimension - Bolt Size fraction	5/8
Dimension - Width mm	89 mm
Dimension - Width inch	3.52 in
Dimension - D inch	1.66 in
Dimension - N inch	0.88 in
Dimension - Length Overall inch	3.50 in

Force Related

Installation Torque Recommended	500 LBS/in in-lb
---------------------------------	---------------------

General

Product Family	MECHANICAL
Material - Hardware	Aluminum
Physical Attribute - Screw Type	Slot
Plated	No
Product Type	Terminal
UPC	781810600306
Type	Bolted Lugs & Terminals

Material	Aluminum
Plating Type	Tin
UPC 12 Digit	781810600306
Hardware Type	3/8 UNC Slotted Set Screw
UPC 14 Digit GTIN	00781810600306

Pallet Quantity	36
Carton Quantity	36
Operational	
Temperature Rating	194

Logistics

Minimum Pack Quantity	1
-----------------------	---

Product Assets

[Catalog \[English\]](#)



A Hubbell brand