



K3A25U4, AL Universal Terminal, 3-Conductor, 4-Hole

By Burndy
Catalog # [K3A25U4](#)

3-Conductor, #14-1/0 AWG, 4-Hole, 3/8" Stud, 1" Spacing, Dual Rated, Tin Plated



Features

- Dual rated lugs
- Constructed from high strength aluminum alloy
- Electro tin plating proving low contact resistance

Specifications

Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	EX
Certification - UL Listed Direct Burial	No
UL Listed	Yes
Certification - CSA Approved	Yes

Conductor

Conductor - AL Str Size	• 8 AWG • 6 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG • 1/0 AWG
Conductor - AL Str Size Range	14 Str.-1/0 AWG
Conductor - Copper Str Size	• 14 AWG • 12 AWG • 10 AWG • 9 AWG • 8 AWG • 7 AWG • 6 AWG • 5 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG • 1/0
Conductor Size	14-1/0 AWG
Number Of Conductors	3
Conductor Type	• AL C Str-Size • CU C Str-Size

Conductor - Copper Str Size Range	14 Str.-1/0 AWG
-----------------------------------	-----------------

Configuration

Physical Attribute - Number of Screws	3
Physical Attribute - Number of Holes	4
Connector Type	Parallel Set-Screw

Dimensions

Dimension - Pad Width inch	2.02 in
Package Height	3.400 in
Dimension - Height mm	22.4 mm
Dimension - Hole Size fraction	7/16
Dimension - Height inch	0.88 in
Dimension - Height fraction	7/8 in
Package Weight	1.330 lb.
Package Length	5.500 in
Dimension - F Width Center to Center inch	1.00 in
Package Width	4.750 in
Dimension - L Length Overall mm	56 mm
Dimension - Width fraction	1-47/50 in
Dimension - Hole Size mm	11 mm
Dimension - Hole Size inch	0.45 in
Dimension - Stud Size inch	3/8 in
Dimension - Bolt Hole Size inch	0.44 in
Dimension - Bolt Size fraction	3/8
Dimension - Width mm	49 mm
Dimension - Width inch	1.64 in
Dimension - D inch	2.09 in
Dimension - N inch	0.34 in
Dimension - Length Overall inch	2.19 in

Force Related

Installation Torque Recommended in-lb	50 LBS/in
---------------------------------------	-----------

General

Material - Hardware	Aluminum
Physical Attribute - Screw Type Plated	Slot Y

UPC	781810370384
Type	Bolted Lugs & Terminals
Material	Aluminum
Plating Type	Tin plated
UPC 12 Digit	781810370384
UPC 14 Digit GTIN	00781810370384

Pallet Quantity	108
Carton Quantity	108

Operational

Temperature Rating	194
--------------------	-----

Product Assets

[Catalog \[English\]](#)

Logistics

Minimum Pack Quantity	1
-----------------------	---



A Hubbell brand