



K3A2U2, AL Universal Terminal, 3-Conductor, 2-Hole

By Burndy
Catalog # [K3A2U2](#)

3-Conductor, 2-Hole, 5/16" Stud, .88" Spacing, #14-2 AWG, Tin Plated, Dual Rated

Features

- Dual rated lugs
- Constructed from high strength aluminum alloy
- Electro tin plating proving low contact resistance

Application

For Aluminum and Copper Conductors

Specifications

Buy American Compliant	Yes
Buy America(n) Qualified	• Buy American Act Compliant (All status valid till December 2026) • BABA Compliant (All status valid till December 2026)
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance	EX
Status	
Certification - UL Listed Direct Burial	No
UL Listed	Yes
Certification - CSA Approved	Yes

Conductor

Conductor - AL Str Size	• 8 AWG • 6 AWG • 4 AWG • 3 AWG • 2 AWG
Conductor - AL Str Size Range	14-2 AWG
Conductor - Copper Str Size	• 14 AWG • 12 AWG • 10 AWG • 9 AWG • 8 AWG • 7 AWG • 6 AWG • 5 AWG • 4 AWG • 3 AWG • 2 AWG
Conductor Size	14-2 AWG
Number Of Conductors	3
Conductor Type	• AL C Str-Size • CU C Str-Size



Conductor - Copper Str Size Range 14-2 AWG

Configuration

Physical Attribute - Number of Screws	3
Physical Attribute - Number of Holes	2
Connector Type	Parallel Set-Screw

Dimensions

Dimension - Pad Width inch	1.64 in
Package Height	3.300 in
Dimension - Height mm	15.7 mm
Dimension - Hole Size fraction	11/32
Dimension - Height inch	0.62 in
Dimension - Height fraction	5/8 in
Package Weight	0.670 lb.
Package Length	3.800 in
Package Width	3.400 in
Dimension - L Length Overall mm	55.62 mm
Dimension - Width fraction	1-59/100 in
Dimension - Hole Size mm	9 mm
Dimension - Hole Size inch	0.34 in
Dimension - Stud Size inch	5/16 in
Dimension - Bolt Hole Size inch	0.57 in
Dimension - Bolt Size fraction	5/16
Dimension - Width mm	40 mm
Dimension - Width inch	1.64 in
Dimension - D inch	1.63 in
Dimension - N inch	0.34 in
Dimension - Length Overall inch	2.19 in

Force Related

Installation Torque Recommended in-lb	50 LBS/in
---------------------------------------	-----------

General

Product Family	MECHANICAL
Material - Hardware	Aluminum
Physical Attribute - Screw Type	Slot
Plated	Yes
Sub Brand	UNIVERSAL TERM
Product Type	Terminal
UPC	781810370360
Type	Bolted Lugs & Terminals

Material	Aluminum	Carton Quantity	216
Plating Type	Tin		
UPC 12 Digit	781810370360	Operational	
UPC 14 Digit GTIN	00781810370360	Temperature Rating	194
Logistics		Product Assets	
Minimum Pack Quantity	1	Catalog [English]	
Pallet Quantity	3240		

