



K3A31U2N, AL Universal Terminal, 3-Conductor, 2-Hole

By Burndy
Catalog # [K3A31U2N](#)

3-Conductor, 2-Hole, 1/2" Stud, 1.75" Spacing, #6 AWG-350 kcmil, Tin Plated

Features

- Dual rated lugs
- Constructed from high strength aluminum alloy
- Electro tin plating proving low contact resistance

Application

For Aluminum and Copper Conductors

Specifications

Certification - UL Recognized	No
Buy American Compliant	Yes
Certification - cULus	No
Buy America(n) Qualified	• Buy America Compliant (All status valid till December 2026) • Buy American Act Compliant (All status valid till December 2026) • BABA Compliant (All status valid till December 2026)
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance	EX
Status	
Certification - UL Listed Direct Burial	No
UL Listed	Yes
Certification - CSA Approved	Yes

Conductor

Conductor - AL Str Size	• 6 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG • 1/0 AWG • 2/0 AWG • 3/0 AWG • 4/0 AWG • 250 kcmil • 266 kcmil • 300 kcmil • 336 kcmil • 350 kcmil
Conductor - AL Str Size Range	6 Str.-350 Kcmil
Conductor - Copper Str Size	• 6 AWG



- 5 AWG
 - 4 AWG
 - 3 AWG
 - 2 AWG
 - 1 AWG
 - 1/0
 - 2/0 AWG
 - 3/0 AWG
 - 4/0 AWG
 - 250 kcmil
 - 300 kcmil
 - 350 kcmil
- Conductor Size 6 AWG-350 KCMIL
- Number Of Conductors 3
- Conductor Type
 - AL C Str-Size
 - CU C Str-Size
- Conductor - Copper Str Size Range 6 Str.-350 Kcmil

Configuration

Physical Attribute - Number of Screws	3
Physical Attribute - Number of Holes	2
Connector Type	Parallel Set-Screw

Dimensions

Dimension - Pad Width inch	3.52 in
Dimension - Height mm	35.1 mm
Dimension - Hole Size fraction	9/16
Dimension - Height inch	1.38 in
Dimension - Height fraction	1.375 in
Dimension - L Length Overall mm	114.3 mm
Dimension - Hole Size mm	14 mm
Dimension - Hole Size inch	0.56 in
Dimension - Stud Size inch	1/2 in
Dimension - Bolt Hole Size inch	0.57 in
Dimension - Bolt Size fraction	1/2
Dimension - Width mm	89 mm
Dimension - Width inch	3.52 in
Dimension - D inch	3.16 in
Dimension - N inch	0.63 in
Dimension - Length Overall inch	4.5 in

Force Related

Installation Torque Recommended	275 LBS/in in-lb
---------------------------------	------------------

General

Product Family	MECHANICAL
Material - Hardware	Aluminum
Physical Attribute - Screw Type	Slot
Plated	Yes
Sub Brand	UNIVERSAL TERM
Product Type	Terminal
UPC	781810601150
Type	Bolted Lugs & Terminals
Material	Aluminum
Plating Type	Tin
UPC 12 Digit	781810601150

UPC 14 Digit GTIN00781810601150

Logistics

Minimum Pack Quantity	1
Pallet Quantity	576
Carton Quantity	18

Operational

Temperature Rating	194
--------------------	-----

Product Assets

[Catalog \[English\]](#)



A Hubbell brand