



K3A31U4N, AL Universal Terminal, 3-Conductor, 4-Hole

By Burndy
Catalog # [K3A31U4N](#)

3-Conductor, 4-Hole, 1/2" Stud, 1.75" Spacing, #6 AWG-350 kcmil, Tin Plated

Features

- Dual rated lugs
- Constructed from high strength aluminum alloy
- Electro tin plating proving low contact resistance

Application

For Aluminum and Copper Conductors

Specifications

Certification - UL Recognized	No
Certification - cULus	No
EU RoHS Indicator	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	NC
Certification - UL Listed Direct Burial	No
UL Listed	Yes
Certification - CSA Approved	Yes

Conductor

Conductor - AL Str Size	• 6 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG • 1/0 AWG • 2/0 AWG • 3/0 AWG • 4/0 AWG • 250 kcmil • 266 kcmil • 300 kcmil • 336 kcmil • 350 kcmil
Conductor - AL Str Size Range	6 Str.-350 Kcmil
Conductor - Copper Str Size	• 6 AWG • 5 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG



Conductor Size	• 1/0 • 2/0 AWG • 3/0 AWG • 4/0 AWG • 250 kcmil • 300 kcmil • 350 kcmil
Number Of Conductors	6 AWG-350 KCMIL 3
Conductor Type	• AL C Str-Size • CU C Str-Size
Conductor - Copper Str Size Range	6 Str.-350 Kcmil

Configuration

Physical Attribute - Number of Screws	3
Physical Attribute - Number of Holes	4
Connector Type	Parallel Set-Screw

Dimensions

Dimension - Pad Width inch	3.52 in
Dimension - Height mm	35.1 mm
Dimension - Hole Size fraction	9/16
Dimension - Height inch	1.38 in
Dimension - Height fraction	1.375 in
Dimension - F Width Center to Center inch	1.75 in
Dimension - L Length Overall mm	114.3 mm
Dimension - Hole Size mm	14 mm
Dimension - Hole Size inch	0.56 in
Dimension - Stud Size inch	1/2 in
Dimension - Bolt Hole Size inch	0.57 in
Dimension - Bolt Size fraction	1/2
Dimension - Width mm	76 mm
Dimension - Width inch	3.52 in
Dimension - D inch	3.00 in
Dimension - N inch	0.63 in
Dimension - Length Overall inch	4.5 in

Force Related

Installation Torque	275 LBS/in
Recommended in-lb	

General

Material - Hardware	Aluminum
Physical Attribute - Screw Type	Slot
Plated	Y
Sub Brand	UNIVERSAL TERM
UPC	781810601174
Type	Bolted Lugs & Terminals
Material	Aluminum
Plating Type	Tin plated
UPC 12 Digit	781810601174
UPC 14 Digit GTIN	00781810601174



A Hubbell brand

Logistics

Pallet Quantity	432
Carton Quantity	18

Operational

Temperature Rating	194
--------------------	-----

Product Assets

[Catalog \[English\]](#)