



KA40U, AL Universal Terminal, 1-Hole, Dual Rated

By Burndy
Catalog # KA40U

Aluminum Universal Terminal, 1 Hole, 300-800 kcmil, 1/2" Stud, 1 Screw, Al/Cu Rated, Tin Plated

Features

- Dual Rated Panelboard Lugs
- High strength extruded aluminum alloy
- Electro tin-plated for low contact resistance
- Rated to 35kV

Application

For Aluminum And Copper Conductors

Specifications

EU RoHS Indicator	Yes
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	EX
Certification - UL Listed Direct Burial	No
UL Listed	Yes
Certification - CSA Approved	Yes

Conductor

Conductor - AL Str Size	• 300 kcmil • 336 kcmil • 350 kcmil • 397 kcmil • 400 kcmil • 450 kcmil • 477 kcmil • 500 kcmil • 550 kcmil • 556 kcmil • 600 kcmil • 636 kcmil • 650 kcmil • 700 kcmil • 715 kcmil • 750 kcmil • 795 kcmil • 800 kcmil
Conductor - AL Str Size Range	300 kcmil-800 kcmil
Conductor - Copper Str Size	• 300 kcmil • 350 kcmil • 400 kcmil • 450 kcmil

Conductor Size	300-800 KCMIL
Number Of Conductors	1
Conductor Type	• CU C Str-Size • AL C Str-Size
Conductor - Copper Str Size Range	300 kcmil-800 kcmil

Configuration

Physical Attribute - Number of Screws	1
Physical Attribute - Number of Holes	1
Connector Type	Terminal

Dimensions

Dimension - Pad Width inch	1.77 in
Package Height	2.250 in
Dimension - Height mm	49.5 mm
Dimension - Height inch	1.95 in
Package Weight	1.750 lb.
Package Length	8.100 in
Package Width	3.400 in
Dimension - L Length Overall mm	89 mm
Dimension - Width fraction	1-3/4 in
Dimension - Hole Size mm	17 mm
Dimension - Hole Size inch	0.66 in
Dimension - Stud Size inch	1/2
Dimension - Bolt Hole Size inch	0.62 in
Dimension - Bolt Size fraction	1/2
Dimension - Width mm	44 mm
Dimension - Width inch	1.75 in
Dimension - D inch	1.85 in
Dimension - N inch	0.81 in
Dimension - Length Overall inch	3.50 in

Force Related

Installation Torque Recommended in-lb	550 LBS/in
---------------------------------------	------------

General

Material - Hardware	Aluminum
Physical Attribute - Screw Type	Allen
Plated	Y
Sub Brand	UNIVERSAL TERM
UPC	781810370308
Type	Bolted Lugs & Terminals
Material	Aluminum
Plating Type	Tin



A Hubbell brand

UPC 14 Digit GTIN 00781810370308

Logistics

Pallet Quantity	1920
Carton Quantity	60

Product Assets

[Catalog \[English\]](#)