



KSU26, Split Bolt Connector with Spacer. Tin Plated

By Burndy
Catalog # [KSU26](#)

Tin plated copper alloy SERVIT with spacer to separate dissimilar conductors

Features

- Tin-plated, high strength copper alloy with spacer
- Spacer separates dissimilar conductors and provides long contact length preventing high pressure point contacts between run and tap conductors

Application

For All Combinations Of Copper, Aluminum, ACSR, AAAC, 5005, And Steel

Specifications

EU RoHS Indicator	Yes
Standards - RoHS Compliance Status	CM
UL Listed	Yes
Certification - CSA Approved	No

Conductor

Conductor - AAAC 5005 Tap Range	30.58 (7) kcmil-123.3 (7) kcmil
Conductor - AAAC 5005 Tap	• 30.58 (7) kcmil • 48.69 (7) kcmil • 77.47 (7) kcmil • 123.3 (7) kcmil
Conductor - AAAC 6201 Run Range	123.3 (7) kcmil
Conductor - AAAC 6201 Run	123.3 (7) kcmil
Conductor - Galvanized Steel Str Size	7/16 (7) in
Conductor - Galvanized Steel Str Size Range	7/16 (7) in
Conductor - AAAC 6201 Tap Range	30.58 (7) kcmil-123.3 (7) kcmil
Conductor - AAAC 6201 Tap	• 30.58 (7) kcmil • 48.69 (7) kcmil • 77.47 (7) kcmil • 123.3 (7) kcmil
Conductor - AL Str Run Range	2 AWG - 2/O AWG
Conductor - AL Str Run	• 2 AWG • 1 AWG • 1/O AWG • 2/O AWG
Conductor - AL Str Tap Range	8 AWG - 2/O AWG
Conductor - AL Str Tap	• 8 AWG • 6 AWG



Conductor - ACSR Str Run Range	• 4 AWG • 3 AWG • 2 AWG • 1 AWG • 1/O AWG • 2/O AWG
Conductor - ACSR Str Run	1 AWG - 1/O AWG
Conductor - ACSR Str Tap Range	• 1 (6/1) Robin AWG • 1/O (6/1) Raven AWG
Conductor - ACSR Str Tap	6 AWG - 1/O AWG
Conductor - Copper Str Run Range	• 6 (6/1) Turkey AWG • 5 (6/1) Thrush AWG • 4 (6/1) Swan AWG • 4 (7/1) Swanate AWG • 3 (6/1) Swallow AWG • 2 (6/1) Sparrow AWG • 2 (7/1) Sparate AWG • 1 (6/1) Robin AWG • 1/O (6/1) Raven AWG
Conductor - Copper Str Run	2 AWG - 2/O AWG
Conductor - Copper Solid Run Range	• 2 AWG • 1 AWG • 1/O • 2/O AWG
Conductor - Copper Solid Run	22
Conductor - AAAC 5005 Run Range	123.3 (7) kcmil
Conductor - AAAC 5005 Run	123.3 (7) kcmil
Conductor Type	• CU C Solid-Run • CU C Str-Run • AL C Str-Run • AAAC C 5005-Run • AAAC C 6201-Run • ACSR C Str-Run • CU C Solid-Tap • CU C Str-Tap • AL C Str-Tap • AAAC C 5005-Tap • AAAC C 6201-Tap • ACSR C Str-Tap • GAL Steel C Str-Size

Conductor - Copper Str Tap Range	8 AWG - 2/0 AWG	Dimension - Cross Flats inch	1.04 in
Conductor - Copper Str Tap	8 AWG 7 AWG 6 AWG 5 AWG 4 AWG 3 AWG 2 AWG 1 AWG 1/0 2/0 AWG	Dimension - Length Overall inch	1.95
Configuration		Force Related	
Connector Type	Split Bolt	Installation Torque Recommended in-lb	385
Dimensions		General	
Package Height	0.000 in	Trade Name	SERVIT®
Package Weight	0.000 lb.	Plated	Y
Package Length	0.000 in	Sub Brand	UNIVERSAL SERVIT
Package Width	0.000 in	UPC	781810036600
Dimension - L Length Overall mm	49 mm	Type	KSU, Universal
Width	0.79 in	Material	Copper
Dimension - Width mm	20 mm	Plating Type	Tin Plated
Dimension - Width inch	0.79 in	UPC 12 Digit	781810036600
		UPC 14 Digit GTIN	00781810036600
		Logistics	
		Pallet Quantity	5800
		Carton Quantity	25
		Product Assets	
		Catalog [English]	

