




NA1744NHQ, Substation - Copper Terminal

By Burndy

Catalog # [NA1744NHQ](#)

Substation Connectors



Features

- Type NA for Copper Tube to Pad
- High copper alloy terminal for joining copper tube to a flat pad
- Letter N on end of the catalog number indicates pad drilled to NEMA standards
- One-wrench installation

Application

Substation

Specifications

Certification - UL Recognized	No
Certification - cULus	No
Certification - ETL	No
Standards - RoHS Compliance Status	EX
UL Listed	No
Certification - CSA Approved	No

Conductor

Number Of Conductors	1
Conductor - Connection Combination	Tube to Flat
Conductor Type	• CU Tube Std-Size • CU Tube EH-Size
Conductor - Copper Tube Std Size Range	1 1/2 IPS
Conductor - Copper Tube Std Size	1 1/2 IPS

Configuration

Physical Attribute - Pad Configuration	4 x 4 - 4 holes
Physical Attribute - Pad Alignment	Offset
Physical Attribute - Number of Holes	4
Connector Type	Terminal

Dimensions

Dimension - Pad Width inch	4.00 in
Package Height	0.000 in



A Hubbell brand

Dimension - Height mm	78.5 mm
Dimension - Hole Size fraction	9/16
Dimension - Height inch	3.09 in
Package Weight	0.000 lb.
Package Length	0.000 in
Dimension - F Width Center to Center inch	1.75 in
Package Width	0.000 in
Dimension - L Length Overall mm	180 mm
Width	4 in
Length	7.07 in
Dimension - Width mm	97 mm
Dimension - Width inch	3.82 in
Dimension - B Length inch	2.69 in
Height	0.5 in
Dimension - D inch	4.00 in
Dimension - N inch	1.12 in
Dimension - Length Overall inch	7.07 in
Dimensions	7.07 in x 4 in x 0.5 in

Force Related

Installation Torque Recommended in-lb	480 LBS/in
---------------------------------------	------------

General

Material - Hardware	DURIUM™ Silicon Bronze
One Wrench Installation	Y
Plated	N
Clamping Element Design	Body and Cap
UPC	781810456880
Material	Copper Alloy
Plating Type	Unplated
UPC 12 Digit	781810456880
UPC 14 Digit GTIN	00781810456880

Logistics

Pallet Quantity	1
Carton Quantity	1

Product Assets

[Catalog \[English\]](#)