



NA18A2N, Substation - Aluminum Bolted Terminal, 2 IPS, 2-Hole

By Burndy
Catalog # [NA18A2N](#)

Cu Alloy Terminal, 2 IPS Al or Cu, 230 kV, 2 Pad Holes, 1.75 IN Spacing, 7.50 IN L, 4.50 IN W, Bolted, Tube to Flat, 0.56 IN Hole Dia

Features

- Type NA-A Aluminum Terminals for Tube to Pad
- Properly proportioned to minimize conductor corrosion due to galvanic action
- When properly used, this item does not require use of bimetallic plates, contact Burndy Technical Support for recommendations
- One-wrench installation

Application

Substation

Specifications


Certification - UL Recognized	No
Certification - cULus	No
Certification - ETL	No
Standards - RoHS Compliance Status	CM
UL Listed	No
Certification - CSA Approved	No

Conductor

Conductor - AL Tube Std Size Range	2 IPS
Conductor - AL Tube Std Size	2 IPS
Number Of Conductors	1
Conductor - Connection Combination	Tube to Flat
Conductor Type	• AL Tube Std-Size • CU Tube Std-Size
Conductor - Copper Tube Std Size Range	2 IPS IPS
Conductor - Copper Tube Std Size	2 IPS IPS

Configuration

Physical Attribute - Pad Orientation	Straight
Physical Attribute - Pad Configuration	2.75 x 3 - 2 holes
Physical Attribute - Pad Alignment	Offset
Physical Attribute - Number of Holes	2



Connector Type	Terminal
Dimensions	
Dimension - G inch	2.05 in
Dimension - Pad Width inch	2.75 in
Package Height	0.000 in
Dimension - Height mm	113.5 mm
Dimension - Hole Size fraction	9/16
Dimension - Height inch	4.47 in
Dimension - Height fraction	4-1/2
Package Weight	0.000 lb.
Package Length	0.000 in
Dimension - F Width Center to Center inch	1.75 in
Package Width	0.000 in
Dimension - L Length Overall mm	191 mm
Dimension - Width fraction	4-1/2 in
Dimension - B Length fraction	4-1/4 in
Dimension - Width mm	114 mm
Dimension - Width inch	4.50 in
Dimension - B Length inch	4.25 in
Dimension - D inch	3.00 in
Dimension - N inch	0.63 in
Dimension - Length Overall inch	7.50 in
Force Related	
Installation Torque Recommended in-lb	480 LBS/in
General	
Material - Hardware	Aluminum
One Wrench Installation	Y
Plated	N
Clamping Element Design UPC	Body and Cap 781810003756
Material	Aluminum Alloy
Plating Type	Unplated
UPC 12 Digit	781810003756
UPC 14 Digit GTIN	00781810003756
Logistics	
Minimum Pack Quantity	1
Pallet Quantity	1



A Hubbell brand