



NA1944N, Substation - Copper Terminal

By Burndy
Catalog # [NA1944N](#)

Substation Connectors

Features

- Type NA for Copper Tube to Pad
- High copper alloy terminal for joining copper tube to a flat pad
- Letter N on end of the catalog number indicates pad drilled to NEMA standards
- One-wrench installation

Application

Substation

Specifications

Certification - ETL	No
Certification - UL Recognized	No
Standards - RoHS Compliance Status	EX
Certification - cULus	No
UL Listed	No
Certification - CSA Approved	No

Conductor


Number Of Conductors	1
Conductor - Connection Combination	Tube to Flat
Conductor Type	• CU Tube Std-Size • CU Tube EH-Size
Conductor - Copper Tube Std Size Range	2 1/2 IPS
Conductor - Copper Tube Std Size	2 1/2 IPS
Conductor - Copper Tube EH Size Range	2 1/2 IPS
Conductor - Copper Tube EH Size	2 1/2 IPS

Configuration

Physical Attribute - Pad Configuration	4 x 4.25 - 4 holes
Physical Attribute - Pad Alignment	Offset
Physical Attribute - Number of Holes	4



A Hubbell brand



Connector Type	Terminal
----------------	----------

Dimensions

Dimension - Pad Width inch	4.00 in
Package Height	0.000 in
Dimension - Height mm	95 mm
Dimension - Hole Size fraction	9/16
Dimension - Height inch	3.74 in
Package Weight	0.000 lb.
Dimension - Width mm	133 mm
Dimension - Width inch	5.24 in
Package Length	0.000 in
Dimension - F Width Center to Center inch	1.75 in
Package Width	0.000 in
Dimension - L Length Overall mm	183 mm
Dimension - B Length inch	2.69 in
Dimension - D inch	4.25 in
Dimension - N inch	1.12 in
Dimension - Length Overall inch	7.19 in

General

Plated	N
Material - Hardware	DURIUM™ Silicon Bronze
One Wrench Installation	Y
Clamping Element Design	Body and Cap
UPC	781810143193
Material	Copper Alloy
Plating Type	Unplated
UPC 12 Digit	781810143193
UPC 14 Digit GTIN	00781810143193

Logistics

Minimum Pack Quantity	1
Pallet Quantity	1
Carton Quantity	1

Product Assets

[Catalog \[English\]](#)