



Q2A1C, 2-Conductor, 2-Hole, Heavy Duty Copper Lug

By Burndy

Catalog # [Q2A1C2](#)

2-Conductor, #4-1 AWG Str, 2-Hole, 3/8" Stud, 1" Spacing, Compact Design



Features

- QIKLUG™ Terminals feature compact size, high copper alloy terminal for joining cables to equipment pads or bars
- Each element accommodates a wide range of cable
- One-wrench installation

Application

For Copper Cable

Specifications

Certification - UL Recognized	No
Buy American Compliant	Contact Manufacturer
Certification - cULus	No
Buy America(n) Qualified	Contact Manufacturer
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance	EX
Status	
Certification - UL Listed Direct Burial	No
UL Listed	Yes
Certification - CSA Approved	No

Conductor

Conductor - Copper Str Size	• 4 AWG • 3 AWG • 2 AWG • 1 AWG
Conductor Size	4-1 AWG
Conductor Type	CU C Str-Size
Conductor - Copper Str Size Range	4 AWG-1 AWG

Configuration

Physical Attribute - Number of Screws	2
Physical Attribute - Number of Holes	2
Connector Type	Dual Clamp

Current

Rating - Minimum Voltage	600
--------------------------	-----

Dimensions

Dimension - Pad Width inch	1.50 in
Package Height	0.000 in
Dimension - Height mm	26.9 mm
Dimension - Hole Size fraction	7/16
Dimension - Height inch	1.06 in
Dimension - Height fraction	1-1/16 in
Package Weight	0.000 lb.
Package Length	0.000 in
Dimension - F Width Center to Center inch	1.00 in
Package Width	0.000 in
Dimension - L Length Overall mm	73 mm
Dimension - Width fraction	1-13/16 in
Dimension - Hole Size mm	11 mm
Dimension - Hole Size inch	0.44 in
Dimension - Stud Size inch	3/8
Dimension - Bolt Size fraction	3/8
Dimension - Width inch	1.81 in
Dimension - B Length inch	0.88 in
Dimension - D inch	1.88 in
Dimension - N inch	0.44 in
Dimension - Length Overall inch	2.88 in

Force Related

Installation Torque Recommended	150 LBS/in in-lb
---------------------------------	------------------

General

Product Family	MECHANICAL
Trade Name	QIKLUG™
Physical Attribute - Screw Type	Hexagonal Bolt
Plated	No
Sub Brand	QIKLUG
Product Type	Terminal
UPC	781810321089
Type	Bolted Lugs & Terminals
Material	Copper
Plating Type	Unplated
UPC 12 Digit	781810321089
UPC 14 Digit GTIN	00781810321089

Logistics

Minimum Pack Quantity	1
Pallet Quantity	432
Carton Quantity	12

Operational

Temperature Rating 194

Product Assets

[Catalog \[English\]](#)

[Installation Manual \[English\]](#)



A Hubbell brand