



Substation - Aluminum Welded Corona Bell

By Burndy
Catalog # [SCB22A](#)

CORONA BELL, 4 IN IPS, 550kV

Features

- Aluminum alloy streamlined, self-shielding corona end bell
- For operation of voltages up to 550kV
- For standard (Schedule 40) and extra heavy (Scheduled 80) tube

Application

Substation

Specifications

Certification - ETL	No
Certification - UL Recognized	No
Standards - RoHS Compliance	EX
Status	
Certification - cULus	No
UL Listed	No
Certification - CSA Approved	No

Conductor

Conductor - AL Tube Std Size	4 IPS
Range	
Conductor - AL Tube Std Size	4 IPS
Conductor Type	AL Tube Std-Size

Configuration

Connector Type	Pipe Cap / End Bell
----------------	---------------------

Dimensions

Dimension - Height mm	0 mm
Dimension - Width mm	305 mm
Dimension - Width inch	12.00 in
Dimension - L Length Overall mm	216 mm
Dimension - Length Overall inch	8.50 in

General

Plated	N
Material - Hardware	Aluminum
UPC	781810164860
Material	Aluminum Alloy
Plating Type	Unplated
UPC 12 Digit	781810164860
UPC 14 Digit GTIN	00781810164860

Logistics

Minimum Pack Quantity	1
-----------------------	---

Product Assets

[Catalog \[English\]](#)