



Substation - Aluminum Welded Corona Bell

By Burndy
Catalog # [SCB83ACG3](#)

CORONA BELL

Features

- Aluminum alloy streamlined, self-shielding corona end bell
- For operation of voltages up to 550kV
- For standard (Schedule 40) and extra heavy (Scheduled 80) tube

Application

Substation

Specifications

Certification - ETL	No
Certification - UL Recognized	No
Standards - RoHS Compliance	CM
Status	
Certification - cULus	No
UL Listed	No
Certification - CSA Approved	No

Conductor

Conductor - AL Tube Std Size	8 OD
Range	
Conductor - AL Tube Std Size	8 OD
Conductor Type	AL Tube Std-Size

Configuration

Connector Type	Pipe Cap / End Bell
----------------	---------------------

Dimensions

Dimension - Height mm	0 mm
Dimension - Width mm	356 mm
Dimension - Width inch	14.00 in
Dimension - L Length Overall mm	267 mm
Dimension - Length Overall inch	10.53 in

General

Plated	N
Material - Hardware	Aluminum
UPC	781810424032
Material	Aluminum Alloy
Plating Type	Unplated
UPC 12 Digit	781810424032
UPC 14 Digit GTIN	00781810424032

Logistics

Minimum Pack Quantity	1
-----------------------	---

Product Assets

[Catalog \[English\]](#)