


UP34R, Heavy Duty Parallel Clamp, Copper or Aluminum

By Burndy
Catalog # [UP34R](#)

Heavy Duty Parallel Clamp



Features

- Heavy Duty Parallel Clamp Type UP-R
- Heavy duty aluminum connector for feeder, subtransmission, and primary distribution
- Massive design and large spacer give maximum protection against galvanic action and overload conditions
- Spacing of U-bolts, tapered bell mouths, and modified V-groove minimize cold flow, eliminate cable damage, and produce wiping action on conductors
- Spacer taps confine cable strands to prevent splaying
- Captured, heat treated aluminum alloy U-bolts
- PENETROX joint compound recommended for all combinations

Specifications

Certification - UL Recognized	No
Certification - cULus	No
Certification - ETL	No
Standards - RoHS Compliance	CM
Status	
UL Listed	No
Certification - CSA Approved	No

Conductor

Conductor - ACSR Cmpt Size A	• 110.8 (12/7) Minorca • 134.6 (12/7) Leghorn • 159 (12/7) Guinea • 176.9 (12/7) Dotterel • 190.8 (12/7) Dorking • 211.3 (12/7) Cochin • 203.2 (16/9) Brahma • 266.8 (18/1) Waxwing • 266.8 (26/7) Owl • 266.8 (26/7) Partridge • 300.0 (26/7) Ostrich • 336.4 (18/1) Merlin • 336.4 (26/7) Linnet • 336.4 (30/7) Oriole • 397.5 (18/1) Chickadee
Conductor - AAAC 5005 Size B	• 155.4 (7) • 195.7 (7) • 246.9 (7) • 312.8 (19) • 394.5 (19) • 465.4 (19)

Conductor - AAAC 5005 Size A 155.4 (7)-465.4 (19)
Range

Conductor - AAAC 5005 Size B 155.4 (7)-465.4 (19)
Range

Conductor - AAAC 6201 Size B 155.4 (7)-465.4 (19)
Range

Conductor - AAAC 6201 Size A

- 155.4 (7)
- 195.7 (7)
- 246.9 (7)
- 312.8 (19)
- 394.5 (19)
- 465.4 (19)

Conductor - AAAC 6201 Size B

- 155.4 (7)
- 195.7 (7)
- 246.9 (7)
- 312.8 (19)
- 394.5 (19)
- 465.4 (19)

Conductor - AAAC 6201 Size A 155.4 (7)-465.4 (19)
Range

Conductor - AL Str Size A

- 3/0
- 4/0
- 250
- 266.8
- 300
- 336.4
- 350
- 397.5
- 400

Conductor - AL Str Size B

- 3/0
- 4/0
- 250
- 266.8
- 300
- 336.4
- 350
- 397.5
- 400

Conductor - AL Str Size A 3/0-400
Range


Conductor - AL Str Size B 3/0-400
Range

Conductor - ACSR Str Size B

- 110.8 (12/7) Minorca
- 134.6 (12/7) Leghorn
- 159 (12/7) Guinea
- 176.9 (12/7) Dotterel
- 190.8 (12/7) Dorking

Conductor - Copper Str Size A	• 211.3 (12/7) Cochin • 203.2 (16/9) Brahma • 266.8 (18/1) Waxwing • 266.8 (26/7) Owl • 266.8 (26/7) Partridge • 300.0 (26/7) Ostrich • 336.4 (18/1) Merlin • 336.4 (26/7) Linnet • 336.4 (30/7) Oriole • 397.5 (18/1) Chickadee
	• 3/0
	• 4/0
	• 250
	• 300
	• 350
	• 400
	• 3/0
	• 4/0
	• 250
Conductor - Copper Str Size B	• 300
	• 350
	• 400
	• 3/0
Conductor - Copper Str Size A Range	• 3/0-400
Conductor - AAAC 5005 Size A	• 155.4 (7)
	• 195.7 (7)
	• 246.9 (7)
	• 312.8 (19)
	• 394.5 (19)
	• 465.4 (19)
Conductor - Copper Str Size B Range	3/0-400

Configuration



Connector Type	Spacer
Dimensions	
Package Height	0.000 in
Dimension - Height mm	117.6 mm
Dimension - Height inch	4.63 in
Dimension - Height fraction	4-17/27 in
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in
Dimension - L Length Overall mm	102 mm
Dimension - Width fraction	2-17/27 in
Dimension - Width mm	67 mm
Dimension - Width inch	2.63 in
Dimension - Length Overall inch	4 in
General	
Material - Hardware	Aluminum Alloy
Plated	N
UPC	781810103586
Material	Aluminum Alloy
Plating Type	Unplated
UPC 14 Digit GTIN	00781810103586

Logistics

Minimum Pack Quantity	4
Pallet Quantity	360
Carton Quantity	10

Product Assets

[Catalog \[English\]](#)