



VA34, Substation - Copper V Type Terminal, Bolted, 300-500 kcmil, 1-Hole

By Burndy
Catalog # [VA34](#)

Cast Cu Alloy VARILUG Terminal, Bolted, 300 - 500 Kcmil, 1 Pad Hole, 0.56" Hole Dia.



Features

- Type VA Copper V Type Terminal is a high copper alloy terminal for joining a wide range of cable to equipment pads or bar
- Particularly suitable for use on extra flexible cable
- One-wrench installation

Application

Substation

Specifications

Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	EX
UL Listed	Yes
Certification - CSA Approved	No

Conductor

Conductor - Copper Str Size	• 300 kcmil • 350 kcmil • 400 kcmil • 450 kcmil • 500 kcmil
Number Of Conductors	1
Conductor - Connection Combination	Cable to Flat
Conductor Type	CU C Str-Size
Conductor - Copper Str Size Range	300 kcmil-500 kcmil

Configuration

Physical Attribute - Pad Orientation	Straight
Physical Attribute - Pad Configuration	1.38 x 1.41 - 1 hole
Physical Attribute - Pad Alignment	Offset
Physical Attribute - Number of Holes	1

Physical Attribute - Number of Clamping Elements	1
Connector Type	Terminal

Dimensions

Dimension - Pad Size inch	1.38 x 1.41
Dimension - Pad Width inch	1.38 in
Package Height	0.000 in
Dimension - Height mm	37.3 mm
Dimension - Hole Size fraction	9/16
Dimension - Height inch	1.47 in
Dimension - Height fraction	3-11/32 in
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in
Dimension - L Length Overall mm	97 mm
Dimension - Width fraction	1-3/8 in
Dimension - Hole Size inch	0.56 in
Dimension - Stud Size inch	1/2
Dimension - Width mm	56 mm
Dimension - Width inch	2.22 in
Dimension - B Length inch	1.31 in
Dimension - D inch	1.41 in
Dimension - N inch	0.81 in
Dimension - Length Overall inch	3.81 in

Force Related

Installation Torque Recommended in-lb	375 LBS/in
---------------------------------------	------------

General

Trade Name	VARILUG™
Material - Hardware	DURIUM™ Silicon Bronze
One Wrench Installation	Y
Plated	N
Clamping Element Design	V Bolt
UPC	781810005507
Type	Bolted Lugs & Terminals
Material	Copper Alloy
Plating Type	Unplated
UPC 12 Digit	781810005507
UPC 14 Digit GTIN	00781810005507

Logistics

Minimum Pack Quantity	1
Pallet Quantity	1008
Carton Quantity	6

Product Assets

[Catalog \[English\]](#)



A Hubbell brand