



6-Ton Latch Head Crimper, Self Cont, D3 Groove, W & X Dies

By Burndy  
Catalog # [Y500CTHS](#)

6-Ton Latch Head Crimper, Self Cont Hydraulic, D3 Groove, Uses W & X Dies

Features

- Permanent functional D3 groove (no die needed)
- Used with W, X, and W-VT style dies
- 180° head rotation
- Enhanced clearance for tap connectors

Application

Crimping

Specifications

|                             |    |
|-----------------------------|----|
| Standards - RoHS Compliance | EX |
| Status                      |    |
| Buy American Compliant      | No |

Conductor

|                 |                                                                                                                                                                                                                                        |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Crimping Ranges | Copper, Aluminum, ACSR, Steel, Copperweld, Alumoweld, 6201, 5005, Compressed, Compact, Stranded and Solid conductors, Installs Splices, Taps or Terminations: #8 - 600 kcmil Copper Str., #8 - 350 kcmil Flex, #8 - 350 kcmil Aluminum |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Dimensions

|        |         |
|--------|---------|
| Length | 18 in   |
| Weight | 7.8 lb. |

|            |                          |
|------------|--------------------------|
| Height     | 2.68 in                  |
| Width      | 5.5 in                   |
| Dimensions | 18 in x 5.5 in x 2.68 in |

Force Related

|                      |       |
|----------------------|-------|
| Crimp Force Capacity | 6 ton |
|----------------------|-------|

General

|                          |                                                                                                                      |
|--------------------------|----------------------------------------------------------------------------------------------------------------------|
| Application - For Use On | Copper, Aluminum, ACSR, Steel, Copperweld, Alumoweld, 6201, 5005, Compressed, Compact, Stranded and Solid Conductors |
| Trade Name               | HYPRESS™                                                                                                             |
| Sub Brand                | HYPRESS                                                                                                              |
| Tool Type                | Self-Contained Hydraulic Crimper                                                                                     |
| Product Type             | 6-Ton                                                                                                                |
| Die Type                 | W Die and X Die                                                                                                      |
| UPC                      | 781810270387                                                                                                         |
| UPC 12 Digit             | 781810270387                                                                                                         |
| UPC 14 Digit GTIN        | 00781810270387                                                                                                       |

Logistics

|                       |                    |
|-----------------------|--------------------|
| Minimum Pack Quantity | 1                  |
| Package Contents      | Tool, Plastic Case |

Product Assets

[Catalog \[English\]](#)