




YC28C28, Copper C-Shape Connector

By Burndy
Catalog # [YC28C28](#)

CU Compression C Shape Compression Connector, 600 Volts to 35 kV,
3/0 Str. - 4/0 Str. (Run & Tap)



Features

- Range-taking connector lowering inventory requirements
- Compact size, easy to tape and insulate connection
- High conductivity wrought copper provides low resistance and excellent electrical conductivity

Application

For Making Tap Or Parallel Copper Connections

Specifications

Certification - UL Recognized	No
Buy American Compliant	Yes
Certification - cULus	No
Buy America(n) Qualified	• Buy America Compliant (All status valid till December 2026) • Buy American Act Compliant (All status valid till December 2026) • BABA Compliant (All status valid till December 2026)
Industry Standard(s)	• UL 486A • UL486B
Certification - ETL	No
Standards - Industry Standards Met	• UL 486A • UL486B
Standards - RoHS Compliance	CM
Status	
UL Listed	Yes
Certification - CSA Approved	No

Conductor

Conductor - Copper Str Run Range	3/0 AWG-4/0 AWG
Conductor - Copper Str Tap Range	3/0 AWG-4/0 AWG

Dimensions

Package Height	0.000 in
Dimension - Height mm	0 mm
Dimension - Height inch	1.56 in
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in
Dimension - L Length Overall mm	27 mm
Dimension - Length Overall inch	1.07 in

General

Product Family	Power Connectors>Copper Compression Terminals & Splices>C Taps>Heavy Wall CRIMPIT™
Trade Name	F or D3
Die Index	No
Plated	CRIMPIT
Sub Brand	Compression
Product Type	781810116302
UPC	YC-C Series
Type	Copper
Material	Unplated
Plating Type	781810116302
UPC 12 Digit	00781810116302
UPC 14 Digit GTIN	

Logistics

Minimum Pack Quantity	1
Pallet Quantity	7400
Carton Quantity	50

Product Assets

[Catalog \[English\]](#)