




YC4C4, Copper C-Shape Connector

By Burndy
Catalog # [YC4C4](#)



CU Compression C Shape Compression Connector, 600 Volts to 35 kV, 6 Sol. - 4 Str. (Run & Tap)

Features

- Range-taking connector lowering inventory requirements
- Compact size, easy to tape and insulate connection
- High conductivity wrought copper provides low resistance and excellent electrical conductivity

Application

For Range Of Copper And Making Tap Or Parallel Copper Connections

Specifications

Certification - UL Recognized	No
Buy American Compliant	No
Certification - cULus	No
Buy America(n) Qualified	BABA Compliant (All status valid till December 2026)
Industry Standard(s)	• UL 486A • UL486B
Certification - ETL	No
Standards - Industry Standards Met	• UL 486A • UL486B
Standards - RoHS Compliance	CM
Status	
UL Listed	Yes
Certification - CSA Approved	No

Conductor

Conductor - Copper Str Run Range	6 Sol. - 4 Str.
Conductor - Copper Solid Run Range	6 Sol. - 4 Str.
Conductor - Copper Solid Tap Range	6 Sol. - 4 Str.
Conductor Type	Cu C Sol-Size
Conductor - Copper Str Tap	4 AWG

Dimensions

Package Height	0.000 in
Dimension - Height mm	0 mm
Dimension - Height inch	0.81 in
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in
Dimension - L Length Overall mm	14 mm
Dimension - Length Overall inch	0.57 in

General

Product Family	Power Connectors>Copper Compression Terminals & Splices>C Taps>Heavy Wall CRIMPIT™
Trade Name	BG or 5/8
Die Index	No
Plated	CRIMPIT
Sub Brand	Compression
Product Type	781810113509
UPC	YC-C Series
Type	Copper
Material	Unplated
Plating Type	781810113509
UPC 12 Digit	00781810113509
UPC 14 Digit GTIN	

Logistics

Minimum Pack Quantity	1
Pallet Quantity	57600
Carton Quantity	100

Product Assets

[Catalog \[English\]](#)