




YC4C6, Copper C-Shape Connector

By Burndy
Catalog # [YC4C6](#)

CU Compression C Shape Compression Connector, 600 Volts to 35 kV,
Run: 6 Sol. - 4 Str., Tap: 6 Sol. - 6 Str.



Features

- Range-taking connector lowering inventory requirements
- Compact size, easy to tape and insulate connection
- High conductivity wrought copper provides low resistance and excellent electrical conductivity

Application

For Making Tap Or Parallel Copper Connections

Specifications

Buy American Compliant	No
Buy America(n) Qualified	BABA Compliant (All status valid till December 2026)
Industry Standard(s)	• UL 486A • UL486B
Standards - Industry Standards Met	• UL 486A • UL486B
Standards - RoHS Compliance	CM
Status	
UL Listed	Yes
Certification - CSA Approved	No

Conductor

Conductor - Copper Str Run Range	6 Sol. - 4 Str.
Conductor - Copper Solid Run Range	6 Sol. - 4 Str.
Conductor - Copper Solid Tap	6 AWG
Conductor Type	Cu C Sol-Size
Conductor - Copper Str Tap	6 AWG

Dimensions

Package Height	0.000 in
Dimension - Height mm	0 mm
Dimension - Height inch	0.76 in
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in
Dimension - L Length Overall mm	14 mm
Dimension - Length Overall inch	0.57 in

General

Product Family	Power Connectors>Copper Compression Terminals & Splices>C Taps>Heavy Wall CRIMPIT™
Trade Name	BG or 5/8
Die Index	No
Plated	CRIMPIT
Sub Brand	Compression
Product Type	781810113752
UPC	YC-C Series
Type	Copper
Material	Unplated
Plating Type	781810113752
UPC 12 Digit	00781810113752
UPC 14 Digit GTIN	

Logistics

Minimum Pack Quantity	1
Pallet Quantity	57600
Carton Quantity	50

Product Assets

[Catalog \[English\]](#)