



YE32P250X125FX, Copper Compression Pin Adapter, 400 kcmil Cu

By Burndy
Catalog # [YE32P250X125FX](#)

Copper Compression Adapter to terminate copper when current capacity is downsized but larger conductor used, 400 kcmil Copper



Features

- Connector:Uninsulated copper compression pin adapter
- Connection: Irreversible and maintenance free
- Long barrel lengths allow for an increased number of crimps, increasing the mechanical strength of the connection
- Material types include: Santoprene or PVC

Application

Typical applications are for voltage drop protection when oversized conductors are used or flex conductor is used

Specifications

Buy American Compliant	Contact Manufacturer
Buy America(n) Qualified	Contact Manufacturer

Conductor

Conductor - Copper Flex G Size	300 KCMIL
Conductor - Copper Str Compact Size	400 KCMIL
Conductor - Copper DLO Size	313 KCMIL
Conductor Size	400 KCMIL
Conductor - Copper Flex H Size	300 KCMIL
Conductor - Copper Flex G Size	300 KCMIL
Range	
Conductor - Material	COPPER
Conductor - Copper Flex K Size	300 KCMIL
Conductor Type	CODE/FLEX
Conductor - Copper Str Size	400 KCMIL
Conductor - Copper Flex I Size	300 KCMIL

Configuration

Connector Type	INLINE PIN
----------------	------------

Current

Voltage Rating	600 V
----------------	-------

Dimensions

Package Height	0.000 in
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in

General

Color Code	Blue
Trade Name	HYPLUG™
UPC	621945644748
Type	Connector
Construction Material - Main Material	Copper
Finish Type	COPPER
	Tin-Plated

Logistics

Pallet Quantity	3600
Carton Quantity	25

Operational

Temperature Rating	90°C
--------------------	------

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)