



YE34P250X125FX, Copper Compression Pin Adapter, 500 kcmil Cu

By Burndy
Catalog # [YE34P250X125FX](#)

Copper Compression Adapter to terminate copper when current capacity is downsized but larger conductor used, 500 kcmil Copper

Features

- Connector:Uninsulated copper compression pin adapter
- Connection: Irreversible and maintenance free
- Long barrel lengths allow for an increased number of crimps, increasing the mechanical strength of the connection
- Material types include: Santoprene or PVC

Application

Typical applications are for voltage drop protection when oversized conductors are used or flex conductor is used

Specifications

Buy American Compliant No

Conductor

Conductor - Copper Flex G Size	350 KCMIL
Conductor - Copper Str Compact Size	500 KCMIL
Conductor - Copper DLO Size	373 KCMIL
Conductor Size	500 KCMIL
Conductor - Copper Flex H Size	350 KCMIL
Conductor - Copper Flex G Size Range	350 KCMIL
Conductor - Material	COPPER
Conductor - Copper Flex K Size	350 KCMIL
Conductor Type	CODE/FLEX
Conductor - Copper Str Size	500 KCMIL
Conductor - Copper Flex I Size	350 KCMIL

Configuration

Connector Type INLINE PIN



Current

Voltage Rating 600 V

Dimensions

Package Height	0.000 in
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in

General

Color Code	Brown
Trade Name	HYPLUG™
Die Index	20
UPC	621945644755
Type	Connector
Construction Material - Main Material	Copper
Finish Type	COPPER Tin-Plated

Logistics

Pallet Quantity	3600
Carton Quantity	25

Operational

Temperature Rating 90°C

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)