

YPC40A32, Figure 6-shaped Connector

By Burndy

Catalog # [YPC40A32](#)

Figure 6 shape connector separates run and tap wires and minimizes galvanic corrosion of conductors, Run ACSR, 5005:556.6 (18-1) - 795 (26-7)



Features

- Figure 6-Shaped Connector
- Separates Run and Tap Wires

Specifications

Certification - ETL	No
Certification - UL Recognized	No
Standards - RoHS Compliance	CM
Status	
Certification - cULus	No
UL Listed	No
Certification - CSA Approved	No

Conductor

Conductor - Copper Str Run Range	600 kcmil-800 kcmil
Conductor - Copper Str Run	• 600 kcmil • 700 kcmil • 750 kcmil • 800 kcmil
Conductor - AL Str Run Range	600 kcmil-800 kcmil
Conductor - AL Str Run	• 600 kcmil • 636 kcmil • 650 kcmil • 700 kcmil • 715 kcmil • 750 kcmil • 795 kcmil • 800 kcmil
Conductor - AL Str Tap Range	2/0 AWG-400 kcmil
Conductor - AL Str Tap	• 2/0 AWG • 3/0 AWG • 4/0 AWG • 250 kcmil • 266 kcmil • 300 kcmil • 336 kcmil • 350 kcmil • 397 kcmil • 400 kcmil
Conductor Type	• AL C Str-Run • CU C Str-Run • CU C Solid-Run • ACSR C Str-Run • AL C Str-Tap

Conductor - ACSR Str Tap Range	• CU C Str-Tap • CU C Solid-Tap • ACSR C Str-Tap
Conductor - Copper Str Tap Range	556.5 kcmil-795 kcmil
Conductor - Copper Str Tap	2/0 AWG-400 kcmil
Conductor - ACSR Str Tap Range	• 2/0 AWG • 3/0 AWG • 4/0 AWG • 250 kcmil • 300 kcmil • 350 kcmil • 400 kcmil
Conductor - ACSR Str Tap Range	2/0 AWG-397.5 kcmil

Dimensions

Package Height	0.000 in
Dimension - Height inch	3.74 in
Package Weight	0.000 lb.
Dimension - Width inch	1.88 in
Package Length	0.000 in
Package Width	0.000 in
Dimension - L Length Overall mm	127 mm
Dimension - Length Overall inch	5 in

General

Plated	N
Trade Name	CRIMPIT™
Die Index	T
UPC	781810138656
Material	Aluminum
Plating Type	Unplated
UPC 12 Digit	781810138656
UPC 14 Digit GTIN	00781810138656

Logistics

Minimum Pack Quantity	1
Pallet Quantity	612
Carton Quantity	9



A Hubbell brand