



YSE10BOX, Nylon Splice For 12 - 10 AWG

By Burndy

Catalog # [YSE10BOX](#)

Nylon Splice For 12 - 10 AWG



Features

- Manufactured from tin plated, seamless electrolytic copper tubing with integral barrel/insulation grip - providing maximum conductivity and tensile strength along with excellent cable support and strain relief
- Split heavy wall insulation grip for stronger insulation grip and strain relief
- Smooth funnel entry for easy wire insertion
- Transparent nylon insulation for easy wire insertion

Application

For Splicing Aircraft And Commercial Flexible Cables

Specifications

Buy American Compliant Certification - cULus	Contact Manufacturer
EU RoHS Indicator	No
Certification - UL Recognized	Yes
Industry Standard(s)	No
Buy America(n) Qualified	UL486
Certification - ETL	Contact Manufacturer
Standards - Industry Standards Met	No
Standards - RoHS Compliance Status	UL486
Certification - CSA Approved	CM
UL Listed	Yes

Conductor

Conductor - Copper Str Size	• 12 • 10
Conductor - Copper Str Aircraft Size	• AN 12 • AN 10
Conductor - Copper Str Aircraft Size Range	AN 12-AN 10
Conductor Size	12 - 10 AWG
Conductor - Copper Str Size Range	12-10
Conductor Type	CU C Str-Size

Configuration

Connector Type	Seamless Butt Splice
----------------	----------------------

Current

Voltage - Maximum	600 V
-------------------	-------

Dimensions

Package Length	0.000 in
Package Width	0.000 in
Package Weight	0.000 lb.
Dimension - Outside Diameter inch	0.21 in
Dimension - L Length Overall mm	29 mm
Package Height	0.000 in
Dimension - Strip Length inch	23/64 in
Dimension - B Length fraction	3/10 in
Dimension - B Length inch	0.30 in
Cable Insulation Diameter Maximum	0.209 in
Dimension - Length Overall inch	1.15 in
Dimension - Diameter Max Size inch	0.22 in

General

Insulation Type	Nylon
Trade Name	INSULINK™
Insulation	Y
Sub Brand	INSULINK
Color Code	Yellow
Plated	Y
Type	YSE
UPC 12 Digit	781810566305
UPC 14 Digit GTIN	00781810566305
Material	Copper
Plating Type	Tin
UPC	781810566305

Logistics

Minimum Pack Quantity	50
Carton Quantity	600
Pallet Quantity	99999

Operational

Temperature Rating	105
--------------------	-----

Product Assets

[Catalog \[English\]](#)



A Hubbell brand