



YSR44FX34FXLTCKITC, Compression
Splice Reducer, Barrel A 750 kcmil, Barrel B
350 kcmil, includes clear heat shrink

By Burndy
Catalog # YSR44FX34FXLTCKITC

CU Splice Reducer, Barrel A 750 kcmil G,H,777 DLO, Barrel B 350
kcmil G,H,I,K,M,373 DLO CU, Kit includes clear heat shrink

Features

- Each splice kit includes one YSR-TC compression in-line splice reducer connector and heat shrink
- Designed configurations allow for copper code-to-code wire connections, copper code-to-flex wire connections, and copper flex-to-flex wire connections
- Barrel is designed with a taper to accommodate a main run wire that is reduced to a smaller tap wire
- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors clearly marked with color coding

Application

Wire Reducing Splice

Specifications

Certification - UL Recognized	No
Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Contact Manufacturer
Certification - ETL	No
Standards - RoHS Compliance	CM
Status	
UL Listed	No
Certification - CSA Approved	No

Conductor

Conductor - Material	COPPER
Wire Size	750 KCMIL-350 KCMIL
Conductor - Copper Flex K Size	350 kcmil
B Range	
Conductor - Copper Flex K Tap	350 KCMIL
Conductor - Copper Flex K Size	750 KCMIL
A	
Conductor - Copper Flex K Size	350 kcmil
B	
Conductor - Copper Flex K Size	750 KCMIL
A Range	
Conductor - Copper Flex M Size	350 kcmil
B	
Conductor - Copper Flex M Size	750 KCMIL
A Range	
Conductor - Copper Flex M Size	350 kcmil
B Range	



Conductor - Copper Flex M Run	750 KCMIL
Conductor - Copper Flex M Size	750 KCMIL
A	
Conductor - Copper Str Size	750 KCMIL-350 KCMIL
Conductor - Copper Flex I Tap	350 KCMIL
Conductor - Copper Flex K Run	750 KCMIL
Conductor - Copper Flex I Size	350 kcmil
B	
Conductor - Copper Flex I Size	350 kcmil
B Range	
Conductor - Copper Flex G Size	750 kcmil
A	
Conductor - Copper Flex G Size	350 kcmil
B	
Conductor - Copper Flex G Size	750 kcmil
A Range	
Conductor - Copper Flex G Run	750 KCMIL
Conductor - Copper Str Size A	750 kcmil
Conductor - Copper Flex H Run	750 KCMIL
Conductor Size	750 KCMIL-350 KCMIL
Conductor - Copper Str Size B	350 kcmil
Conductor - Copper Flex H Size	750 kcmil
A	
Conductor - Copper Str Size A	750 kcmil
Range	
Conductor - Copper Flex G Size	350 kcmil
B Range	
Conductor - Copper Flex G Tap	350 KCMIL
Conductor - Copper Flex M Tap	350 KCMIL
Conductor Type	FLEX
Conductor - Copper Flex H Tap	350 KCMIL
Conductor - Copper Flex I Run	750 KCMIL
Conductor - Copper Flex H Size	350 kcmil
B	
Conductor - Copper Str Size B	350 kcmil
Range	
Conductor - Copper Flex H Size	750 kcmil
A Range	
Conductor - Copper Flex H Size	350 kcmil
B Range	
Conductor - Copper Flex I Size	750 KCMIL
A	
Conductor - Copper Flex I Size	750 KCMIL
A Range	

Configuration

Connector Type STANDARD BARREL KITS

Current


Voltage Rating 35 kV
Voltage - Maximum 35000

Dimensions

Package Height 0.000 in
Package Weight 0.000 lb.
Package Length 0.000 in
Package Width 0.000 in
Dimension - L Length Overall 125 mm
mm
Dimension - Strip Length inch 1.96 in
Dimension - B Length fraction 2-1/16 in
Dimension - B Length inch 2.09 in
Dimension - Length BB inch 1.69 in
Dimension - Length Overall 4.91 in
inch

General

Trade Name HYREDUCER™
Die Index L115/19
Die Index - Element A L115
Die Index - Element B • 19
 • L80
Die Index Run Side L115
Die Index Tap Side • 19



Feature - Barrel Type • L80
Feature - Barrel Style Standard
Plated Skived
Color Code Y
Sub Brand Yellow, Blue
UPC HYREDUCER
Color Code - Side B 781810466216
Color Code - Side A Blue
Type Yellow
Construction Material - Main YSR-TC
Material Copper
Plating Type Copper
Finish Type Tin - Electro Plated
UPC 12 Digit Tin-Plated
UPC 14 Digit GTIN 781810466216
 00781810466216

Logistics

Minimum Pack Quantity 1
Pallet Quantity 540
Carton Quantity 6

Operational

Temperature Rating 194

Product Assets

[Catalog \[English\]](#)
[Installation Manual \[French, English\]](#)