

Eaton FWC-20A10F

Catalog Number: FWC-20A10F

Eaton Bussmann series FWC high speed cylindrical fuse, 500V, 20A, 200 kAIC Vac, 50 kAIC at 700 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end

General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed cylindrical fuse	FWC-20A10F
	UPC
	051712796460
EAN	Product Length/Depth
5027590499354	38 mm
Product Height	Product Width
11 mm	11 mm
Product Weight	Warranty
8.8 g	Not Applicable
Compliances	Certifications
CE Marked	CSA Certified
RoHS Compliant	UL Recognized



Product specifications

Fuse indicator

Other

Interrupt rating

200 kAIC Vac

Construction size

10 x 38 mm

Clearing (I2T)

260

Connection

Ferrule end x ferrule end

Material

Ceramic

Release characteristic

Other

Amperage Rating

20 A

Frequency rating - max

62 Hz

Utilization category

aR (accompanied semiconductor protection)

Watt losses

4.8 W

Fuse type

FWC-A10F

Accessories

BMM Fuse block

CHM modular fuse holder

Type

High speed fuse

Fuse shape

Cylindrical

Breaking capacity

200 kA

Fuse size

10 x 38 mm

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Compliance information

UKCA FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

CE FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

Specifications and datasheets

Eaton Specification Sheet - FWC-20A10F

Technical data sheets

720011 FWC

Frequency rating - min

45 Hz

Class

Class aR

Pre arc (I2T)

34

Voltage rating

600 V

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Voltage type

AC/DC

Packaging type

Standard



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia