## Impact 3/8", 7/16", 1/2" & 3/4"

# The CP82 Series

COMFORTABLE, ROBUST & COMPACT

- Very low noise, very limited vibration and lightweight for operator comfort
- Durable and reliable for industrial maintenance applications
- Compact for easy access in confined areas
- From 3/8" to 3/4" square drives with Ring/Dual and pin versions

## CP8222-P

3/8

### FEATURES

- Powerful & durable twin hammer clutch
- Composite body and aluminum clutch housing
- 3 power settings in forward & full power in reverse

**CP8222-P**

**CP8222-R**
*Same features as CP8222-P with ring retainer*

## CP8232-QC

7/16 HEX

### FEATURES

- Powerful & durable twin hammer clutch
- Composite body and aluminum clutch housing
- 3 power settings in forward & full power in reverse

CP8222-P

See accessories and dimensions on pages 29-31

GENERAL MAINTENANCE | INDUSTRIAL MAINTENANCE & PRODUCTION | SUPER INDUSTRIAL

| MODEL | PART NUMBER | DRIVE | BLOWS PER MIN | FREE SPEED | WORKING TORQUE (FW) | | MAX TORQUE (REV) | | NET WEIGHT | | LENGTH | | AIR CONS. @LOAD | | VIBRATION LEVEL ISO 28927 (M/S2) | | SOUND PRESS. | SOUND POWER | AIR INLET |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | in. | | rpm | ft.lb | Nm | ft.lb | Nm | lb | kg | in. | mm | cfm | l/s | a | K | ISO 15744 - dB(A) | | in. |
| CP8222-P | **615 159 0180** | 3/8 | 1,250 | 11,500 | 60-295 | 80-400 | 332 | 450 | 2.6 | 1.2 | 7 | 177 | 21.2 | 10 | 5.8 | 2.4 | 89 | 100 | 1/4 |
| CP8222-R | **615 159 0230** | 3/8 | 1,250 | 11,500 | 60-295 | 80-400 | 332 | 450 | 2.6 | 1.2 | 7 | 177 | 21.2 | 10 | 5.8 | 2.4 | 89 | 100 | 1/4 |
| CP8232-QC | **615 159 0190** | 7/16" Hex. | 1,250 | 11,500 | 60-295 | 80-400 | 332 | 450 | 3.1 | 1.4 | 7 | 177 | 21.2 | 10 | 6.6 | 3.2 | 89 | 100 | 1/4 |

*All models: Hose int. 3/8" (10mm) - @90 PSI (@6.3 Bar)*

*Listed specifications are for reference only. Please check documents in each tool.*