



General Information



Danfoss heat shrink splice technology. The end-termination connection is sealed with heat shrink tubes. Danfoss heat shrink splice technology can be used to establish end-termination. It is suitable for the following self-regulating trace heaters:

- Danfoss PX Pipe Trace Heating System
- Danfoss RX-C Roof and Gutter De-Icing System

Ordering Information

Part No.	Description	For Use With
088L1457	End-Termination (heat shrink technology connection system)	PX Pipe Trace Heating Systems
		RX-C Roof & Gutter De-Icing System

Technical Data

Ambient Temperature Range:	-4°F to +185°F/ -20°C to +85°C
Max. Operating Temperature End Cap:	185°F/ 85°C
Protection Class:	NEMA Type 4X

Kit Contents & Typical Application

	No.	Component	Qty.	Designation	Dimensions
 <p>5 x End-termination heat shrink technology for Danfoss PX / RX trace heaters</p>	1		5 x	Heat shrink tube for end-termination	Length: ¾" (20 mm) Diameter: ½" (12 mm)
	2		5 x	Outer heat shrink tube for end-termination	Length: 2 ¾" (70 mm) Diameter: ¾" (19 mm)
	3		5 x	Terminal clamp	-

Technical Services

For technical questions, please contact Danfoss Heating Division North America at **1-888-326-3677 (option 3)**. More information on Danfoss Electric Heating products is available at **LX.Danfoss.com**.

Danfoss can accept no responsibility for possible errors in catalogs, brochures, other printed materials, and website information. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alteration can be made without subsequent changes being necessary in specifications already agreed upon. All trademarks in this material are property of the respective companies. Danfoss and Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



**Danfoss**  
Toll Free: 1-888-326-3677  
Fax: 416-352-5981  
www.LX.Danfoss.com