

Non-Metallic Raceway, BaseTrak Series, 1 Channel Split Cover, 10' Length

By Hubbell Premise Wiring
Catalog # [PB2SPL10](#)



Non-Metallic Raceway BaseTrak, 1 Channel Split Cover, 10'

Features

- UL Listed and CSA Certified to 600 volts
- Single and two channel latching raceways are dual-rated for both power and data applications, reducing inventory requirements

Performance

Environmental - Flame Rating - UL94V-0, Environmental - Temperature Range - -25.6° to 158° F

Specifications

Non Hazardous Location Industry Standard(s)	Non Hazardous • CSA Standard C22.2 no. 62 • E118895 / E119190 • UL Standard UL 5A
EU RoHS Indicator	No

Configuration

Knockouts	None
-----------	------

Dimensions

Width	4.5 in
Height	1.42 in
Length	10 ft

Dimensions

10 ft x 4.5 in x 1.42 in

General

Item Type	PB2, 2-Channel BaseTrak
Construction Type	Extruded Plastic
Enclosure Type	Cover Only, Split Cover
Series	NEMA 1 Rating
Cover Type	PB2
Material	Removable
Specifications	Thermoplastic • Crush Resistance - 300 lbs. • Impact Resistance - 5 ft. lbs. • Length - 10 ft. (3m) • Material - UV Stabilized PVC
UPC	783585310046
Style	Two Channel
Color	Office White

Logistics

Carton Quantity	120
-----------------	-----

Product Assets

- [Catalog \[English\]](#)
[Catalog \[English\]](#)
[Catalog Page \[English\]](#)