Straight Blade Devices

20A, 125V, 2 Pole, 3 Wire Grounding

Straight and Right Angle Pigtailed Terminal

Features

- Transparent housing to inspect contacts
- Audible SNAP, indicates solid connection
- Reduces installation time
- Fully insulated design

Ordering Information

Description	Wire Type	UPC Number	Catalog Number
Right angle, clear terminal with 6-inch leads	Stranded with WAGO	783585541198	**SNAP2RAM2**

Listings

UL Listed to UL498 File No. E2186
Certified to CSA, C22.2, No. 42 File 285
Fed. Spec. W-C-596

Specifications

Contact	Brass
Terminal Body	PBT
Wire	#12 AWG, T90 Nylon FT-1, PVC 90°C (min)
Push wire Connectors	(2) WAGO 773-164, (1) WAGO 773-114



Performance

Electrical

Current Interrupting	Receptacle certified for current interrupting at full rated current
Dielectric Voltage	Withstands 2,000V minimum

Mechanical

Terminal Identification	Terminal Wire Leads- Identified in accordance with UL 498

Environmental

Flammability	UL 94V-2
Operating Temperature	Maximum continuous 75°C; minimum -40°C (w/o impact)

Complementary Products

Mating Receptacle	Hubbell SNAPConnect® Receptacle

Online Resources

Customer Sales Drawing
eCatalog
Installation Instructions

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484
Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

Wiring Device-Kellems